

RBGL: R interface to boost graph library

VJ Carey `stvjc@channing.harvard.edu`

October 16, 2005

Summary. An interface from R to the Boost Graph Library (BGL, an alternative to STL programming for mathematical graph objects) is described. *This 2003 update employs the graph class of Bioconductor.*

Contents

1	Working with the Bioconductor graph class	1
2	Algorithms supported by RBGL	2
2.1	Topological sort	2
2.2	Kruskal's minimum spanning tree	3
2.3	Depth first search	3
2.4	Breadth first search	5
2.5	Dijkstra's shortest paths	6
2.6	Connected components	9
2.7	Strongly connected components	9
2.8	Edge connectivity and minimum disconnecting set	10
2.9	Min-Cut	10

1 Working with the Bioconductor graph class

An example object representing file dependencies is included, as shown in Figure 1.

```
> library(RBGL)
```

```
Loading required package: graph
```

```
Loading required package: cluster
```

```
Loading required package: Ruuid
```

```
> library(Rgraphviz)
```

```
> data(FileDep)
```

```
> print(FileDep)
```




Figure 1: File dependency digraph example from Boost library.

A graphNEL graph with directed edges

Number of Nodes = 15

Number of Edges = 19

2 Algorithms supported by RBGL

2.1 Topological sort

The `tsort` function will return the indices of vertices in topological sort order:

```

> ts <- tsort(FileDep)
> print(nodes(FileDep)[ts + 1])

```

```

[1] "zow_h"      "boz_h"      "zig_cpp"    "zig_o"      "dax_h"
[6] "yow_h"      "zag_cpp"    "zag_o"      "bar_cpp"    "bar_o"
[11] "foo_cpp"    "foo_o"      "libfoobar_a" "libzigzag_a" "killerapp"

```

Note that if the input graph is not a DAG, BGL `topological_sort` will check this and throw 'not a dag'. This is crudely captured in the interface (a message is written to the console and zeroes are returned).

```

#FD2 <- FileDep
# now introduce a cycle
#FD2@edgeL[["bar_cpp"]]$edges <- c(8,1)
#tsort(FD2)

```

2.2 Kruskal's minimum spanning tree

Function `mstree.kruskal` just returns a list of edges, weights and nodes determining the minimum spanning tree (MST) by Kruskal's algorithm.

```

> km <- fromGXL(file(system.file("GXL/kmstEx.gxl", package = "graph")))

```

Loading required package: XML

```

> print(mstree.kruskal(km))

```

```

$edgeList
      [,1] [,2] [,3] [,4]
[1,]    1    4    5    2
[2,]    3    5    1    4

```

```

$weights
      [,1] [,2] [,3] [,4]
[1,]    1    1    1    1

```

```

$nodes
[1] "A" "B" "C" "D" "E"

```

2.3 Depth first search

The `dfs` function returns a list of node indices by discovery and finish order.

```

> df <- fromGXL(file(system.file("XML/dfsex.gxl", package = "RBGL")))
> print(o <- dfs(df))

```




Figure 2: Kruskal MST example from Boost library.




Figure 3: DFS example from Boost library.

```

$discovered
[1] 1 2 5 4 3 6

```

```

$finish
[1] 4 5 2 1 6 3

```

Here is the list of nodes in DFS discovery order.

```

> print(nodes(df)[o$discovered])
[1] "u" "v" "y" "x" "w" "z"

```


2.4 Breadth first search

The `bfs` function returns a vector of node indices for a breadth-first search (BFS) starting at the node indexed by `init.node`.

```
> bf <- fromGXL(file(system.file("XML/bfsex.gxl", package = "RBGL")))
> print(o <- bfs(bf, nodes(bf)[2]))
```

```
[1] 2 6 1 3 7 5 4 8
```

```
> z <- plot(bf)
```



The nodes in BFS

order starting with the second node are

```
> print(nodes(bf)[o])
```

```
[1] "s" "w" "r" "t" "x" "v" "u" "y"
```

2.5 Dijkstra's shortest paths

```
> dd <- fromGXL(file(system.file("XML/dijkex.gxl", package = "RBGL")))
> print(dijkstra.sp(dd))
```

```
$distances
```

```
A B C D E
```

```
0 6 1 4 5
```

```
$penult
```

```
A B C D E
```

```
1 5 1 3 4
```

```
$start
```

```
A
```

```
1
```

```
> ospf <- fromGXL(file(system.file("XML/ospf.gxl", package = "RBGL")))
```

```
> dijkstra.sp(ospf, nodes(ospf)[6])
```

```
$distances
```

RT1	RT2	RT3	RT4	RT5	RT6	RT7	RT8	RT9	RT10	RT11	RT12	N1	N2	N3	N4
7	7	6	7	6	0	8	8	11	7	10	11	10	10	7	8
N6	N7	N8	N9	N10	N11	N12	N13	N14	N15	H1					
8	12	10	11	13	14	10	14	14	17	21					

```
$penult
```

RT1	RT2	RT3	RT4	RT5	RT6	RT7	RT8	RT9	RT10	RT11	RT12	N1	N2	N3	N4
15	15	6	15	6	6	17	17	20	6	19	20	1	2	3	3
N6	N7	N8	N9	N10	N11	N12	N13	N14	N15	H1					
10	8	10	11	12	9	7	5	5	7	12					

```
$start
```

```
RT6
```

```
6
```

```
> sp.between(ospf, "RT6", "RT1")
```

```
$"RT6:RT1"
```

```
$"RT6:RT1"$path
```

```
[1] "RT6" "RT3" "N3" "RT1"
```

```
$"RT6:RT1"$length
```

```
[1] NA
```

```
$"RT6:RT1"$pweights
```

RT6->RT3	RT3->N3	N3->RT1
NA	NA	NA




Figure 4: Network example from BGL.


```
> dd <- fromGXL(file(system.file("XML/dijkex.gxl", package = "RBGL")))
> print(dijkstra.sp(dd))
```

```
$distances
A B C D E
0 6 1 4 5
```

```
$penult
A B C D E
1 5 1 3 4
```

```
$start
A
1
```

2.6 Connected components

```
> km <- fromGXL(file(system.file("GXL/kmstEx.gxl", package = "graph")))
> km@nodes <- c(km@nodes, "F", "G", "H")
> km@edgeL$F <- list(edges = numeric(0))
> km@edgeL$G <- list(edges = 8, weights = 1)
> km@edgeL$H <- list(edges = 7, weights = 1)
> km@edgemode <- "undirected"
> print(connectedComp(ugraph(km)))
```

```
$"1"
[1] "A" "B" "C" "D" "E"
```

```
$"2"
[1] "F"
```

```
$"3"
[1] "G" "H"
```

2.7 Strongly connected components

```
> km <- fromGXL(file(system.file("GXL/kmstEx.gxl", package = "graph")))
> km@nodes <- c(km@nodes, "F", "G", "H")
> km@edgeL$F <- list(edges = numeric(0))
> km@edgeL$G <- list(edges = 8, weights = 1)
> km@edgeL$H <- list(edges = 7, weights = 1)
> km@edgemode <- "directed"
> print(strongComp(km))
```

```
$"1"  
[1] "A" "B" "C" "D" "E"
```

```
$"2"  
[1] "F"
```

```
$"3"  
[1] "G" "H"
```

2.8 Edge connectivity and minimum disconnecting set

```
> coex <- fromGXL(file(system.file("XML/conn.gxl", package = "RBGL")))  
> dcoex <- coex  
> dcoex@edgemode <- "directed"  
> udcoex <- ugraph(dcoex)
```

```
> print(edgeConnectivity(coex))
```

```
$connectivity  
[1] 2
```

```
$minDisconSet  
$minDisconSet[[1]]  
[1] "D" "E"
```

```
$minDisconSet[[2]]  
[1] "D" "H"
```

2.9 Min-Cut

```
> coex <- fromGXL(file(system.file("XML/conn.gxl", package = "RBGL")))  
> dcoex <- coex  
> dcoex@edgemode <- "directed"  
> udcoex <- ugraph(dcoex)
```

```
> print(minCut(coex))
```

```
$mincut  
[1] 2
```

```
$S
```




Figure 5: Edge connectivity example.




Figure 6: min-cut example.

```
[1] 1 2 3 4
```

```
$"V-S"
```

```
[1] 5 6 7 8
```