# **ZyAIR B-500**

## 802.11b Wireless Access Point



Set your network free with an affordable price. The 802.11b-compatible ZyXEL's ZyAlR B-500 delivers a secure, reliable and easy-to-use wireless connection throughout your home or small office. By connecting the ZyAlR B-500 wireless Access Point to your wired network, you can enjoy surfing Internet anywhere in your house with no cabling hassle. Meanwhile, the robust security ensures your Internet connection is protected. The ZyAlR B-500 is the ideal solution for your wireless Internet experience.

## Benefits

## **Maximum Freedom of Mobility with Higher Speed**

ZyXEL's wireless Access Point offers you the maximum mobility of roaming in your office or home. No matter where you are, you can easily and securely access Internet resources, emails; or share large files, MP3 and videos through wireless Access Points. What's more, you can even break the 11Mbps speed barrier of the 802.11b wireless standard to reach 27.5Mbps with proprietary ZyAIR client adapters.

## **High Link Sensitivity and Better Radio Coverage**

Application Diagram

ZyXEL Ethernet Adapte

You can extend your wireless reach by utilizing MDT (Multi-path Decoding Technology), which is capable of overcoming the physical limitations to the signal strength, thus achieve a better three-dimensional radio coverage with more persistent connections and less communication blind spots within range.

## **Enhanced Wireless Security**

ZyXEL's wireless Access Point supports both basic 64/128-bit WEP encryption and up-to-date enhanced wireless security with 802.1x authentication and Wi-Fi Protected Access (WPA\*). Additional MAC address filtering shields wireless network from unauthorized users' entries and assures your wireless communication is protected.

## **Easy Installation and Use**

A user-friendly web-based configurator helps you easily configure ZyXEL's wireless Access Point to build a wireless network effortlessly.

Server

Router

DSL/Cable Modem

DSL/Cable Modem

DSL/Cable Modem

DSL/Cable Modem

Router

ZyXEL CardBus Card

Router

ZyXEL CardBus Card

S02.11b Wireless
Access Point (ZyAIR B-500)

ZyXEL USB Stick

ZyXEL USB Stick



ZyXEL Ethernet Adapte

## Features

- IEEE 802.11b-compliant specification; also forward compatible with 802.11g
- Higher transmission speed up to 27.5Mbps (compatible with ZyAIR B-122/B-320)
- 64/128-bit WEP encryption; IEEE 802.1x security and WPA\* support

- · Built-in local server to authenticate wireless users without interacting RADIUS server (32 users)
- · MAC address filtering through WLAN (support 32 users)
- Supports DHCP client and relay to get/ pass IP address from/ to DHCP server via WAN port
- MDT technology to overcome the physical limitations to the signal strength
- FTP/TFTP firmware upgradeable and configuration can be backup and restored
- Supports SNMP v2c with MIB II
- User-friendly web-based configuration

## Specifications

## **Technical Specifications**

- Standard Compliance
  - IEEE 802.11
  - IEEE 802.11b
  - IEEE 802.3 and 802.3u
  - IEEE 802 1x
  - Wi-Fi certificate
- Data Rate
- 16.5M/11Mbps/5.5Mbps/2Mbps/ 1Mbps (auto fallback)
- Frequency range
  - 2.4~2.4835GHz (Industrial Scientific Medical Band
- Modulation Technique
  - Direct Sequence Spread Spectrum, BPQSK, QPSK/CCK
- Output Power:17dBm (typical)
- Receive Sensitivity: -84dBm
- Coverage Area
  - Indoor: 50M@16.5Mbps 80M@5.5Mbps or lower

Outdoor:

150M@16.5Mbps 300M@5.5Mbps or lower

- Bit Error Rate: 1E-5@-83dBm
- Channels
  - USA (1~11 Channel)
  - Europe (1~13 Channel)
  - Japan (1~14 Channel)

## **Hardware Specifications**

- Ethernet Interface
  - One 10/100 BASE-T RJ-45 Ethernet connector
- 1 external dipole antenna
- Reset Button
  - Restore to the factory default settings
- LEDs
  - PWR/SYS
  - Ethernet Link
  - ■WLAN
- Power Requirements
- ■9VAC@1Amp Max.

## **Operating Environment**

• Operating Temperature: 5 ~ 50°C

• Storage Temperature: -20 ~ 55°C

• Operating Humidity: 10 ~ 90% RH

• Storage Humidity: 5 ~ 95% RH

## **Physical Specification**

• Dimensions: 120(L) x 105(D) x 35(H) mm

• Weight: 180g

## **System Requirement**

- Broadband (cable, DSL, satellite or wireless) Internet service and modem with Ethernet RJ-45 connector
- Ethernet connection (adapter or
- Windows, Mac or Linux based operating system
- Internet Explorer 4.0 or later

## Connectors







Corporate Headquarters ZyXEL Communications Tel: +886-3-578-3942 Fax: +886-3-578-2439 Email: sales@zyxel.com.tw http://www.zyxel.com http://www.zyxel.com.tw

North America ZyXEL Communications Inc Tel: +1-714-632-0882 Fax: +1-714-632-0858 Email: sales@zyxel.com http://www.us.zvxel.e

**Germany ZyXEL Deutschland GmbH.**Tel: +49 2405 6909 0
Fax: +49 2405 6909 99 Email: sales@zyxel.de

Denmark ZyXEL Communicati Tel: +45 39 55 07 00 Fax: +45 39 55 07 07 Email: sales@zyxel.dk http://www.zyxel.dk

Norway ZyXEL Communicati Tel: +47 22 80 61 80 Fax: +47 22 80 61 81 Email: sales@zyxel.no http://www.zyxel.no

Sweden ZyXEL Communications A/S Tel: +46 31 744 7700 Fax: +46 31 744 7701 Email: sales@zyxel.se

Finland ZyXEL Communicatio Tel: +358-9-4780 8400 Fax: +358-9-4780 8448 Email: sales@zyxel.fi

<sup>\*</sup> for future release