

# Prestige 964 Cable Modem

## DOCSIS 2.0 and 1.1 Based



ZyXEL's Prestige 964 Cable Modem leverages the DOCSIS 2.0 Advanced Time Division Multiple Access (A-TDMA) and synchronous Code Division Multiple Access (S-CDMA) technologies with 3 times upstream capacity than DOCSIS 1.1/1.0 systems. The Prestige 964 is interoperable and backward compatible with DOCSIS 1.1 and 1.0 system so cable operators can rapidly deploy the Prestige 964 today for a timely transition in continuous service without interruption. The flexibility of Prestige 964 allows cable operators to maximize the today's infrastructure investments and offer higher bandwidth service for the tomorrow's requirements concurrently.

Prestige 964 incorporates valuable features such as simplified troubleshooting with front panel status indicator LEDs, dual USB and Ethernet connection transparently, remote status monitoring over the cable network, proven reliability and quality, and easy plug & play installation. What's more, Prestige 964 has new compact stylish design to meet tight space installation requirements and is priced competitively.

### Benefits

- DOCSIS™ 2.0 CableLab® Certification
- DOCSIS 1.1/1.0 backward compatible to current investment
- Integrated A-TDMA and S-CDMA technology-capable of providing up to 30 Mbps upstream data rate
- New compact stylish design to meet tight space installation requirements
- Remote management via SNMP
- 10/100 Base-T Ethernet and USB connectivity
- Bridged Ethernet and USB connection allows communications between USB device and Ethernet LAN
- OS Compatibility
  - For Ethernet connectivity: Windows® 95/98/2000/ME/XP, Macintosh®, Linux and UNIX
  - For USB connectivity drivers: Window® 98/2000/ME/XP
- Front panel LEDs and web-based diagnostic interface for easy troubleshooting
- Remote status monitoring over the cable network
- Supports up to 32 users (1 via USB and up to 31 via Ethernet or 32 users on Ethernet)
- Always on, always connected to the Internet

### Features & Specifications

#### Downstream

- Operating Frequency Range: 88 MHz to 860 MHz
- Channel Bandwidth: 6MHz
- Input Impedance: 75ohms (Nominal)
- Modulation: 64QAM or 256QAM
- Maximum Data Rate: 38 Mbps
- Symbol Rates: 64 QAM (5.069 Msym/s)  
256 QAM (5.361 Msym/s)
- Operating Level Range: -15 dBmV to +15 dBmV

#### CPE Network Interface

- Ethernet 10/100 BaseT, USB

#### Security

- BPI, BPI+
- DOCSIS Packet Filter

#### Network Management

- Web-based Diagnostics Interface
- SNMP V1, V2 & V3
- Remote Status Monitoring
- Up to 32 Users (1 via USB and up to 31 via Ethernet or 32 users on Ethernet)

#### Electrical Features

- Power consumption: 5 Vor9VDC @  
1.3 Amps (typical)
- Power Adaptor  
North America: 120 VAC, +/- 5%, 60 Hz  
Europe: 230 VAC, +/- 5%, 50~60 Hz

\* With A-TDMA or S-CDMA enabled CMTS

\*\* Speed of 30 Mbps is attainable only with A-TDMA or S-CDMA technology.

#### Upstream

- Operating Frequency Range: 5 MHz to 42 MHz (edge to edge)
- Bandwidth: 200 KHz /400 KHz /800 KHz  
/1.6MHz /3.2 MHz /6.4\*MHz
- Output Impedance: 75 ohm (Nominal)
- Modulation: 8\*/16/32\*/64\*/128\* QAM or QPSK
- Maximum Data Rate: 30 Mbps\*\*
- Symbol Rates: 160, 320, 640, 1280, 2560  
and 5120\* ksym/s
- Operating Level Range:  
A-TDMA:  
+8 to +54 dBmV (32QAM, 64QAM)  
+8 to +55 dBmV (8 QAM, 16QAM)  
+8 to +58 dBmV (QPSK)  
S-CDMA:  
+8 to +53 dBmV (all modulations)

#### Cable WAN Interface

- F-connector, female 75 ohm

#### Network Protocol

- User MAC Protocol: Ethernet / IEEE802.3; IEEE802.3u
- Transparent Bridging

#### Mechanical & Environment

- LEDs: PWR, SYS, LAN, USB, DATA, CABLE
- Dimension: 197(W) x 143(D) x 31(H) mm  
7.76(W) x 5.63(D) x 1.22(H) inches
- Operating Temperature: 0°C to +40°C (32°F to 104°F)
- Storage Temperature: -30°C to +60°C (-22°F to 156°F)
- Humidity: 5% to 90% Non-condensing

### Rear Panel

- Female "F" Type RF Connector to CATV network
- USB Series B Connector to computer
- RJ-45 Connector to the 10M/100M Hub, Switch or Computer



### Package Includes

- Prestige 964 Cable Modem
- Ethernet cable
- USB cable
- Power adaptor
- Installation CD-ROM with USB drivers
- Read Me First
- 2-year Standard Limited Warranty



<b>Corporate Headquarters</b> ZyXEL Communications Co. Tel: +886-3-578-3942 +886-3-480-8163 Fax: +886-3-578-2439 +886-3-499-3173 Email: sales@zyxel.com.tw sales@zygate.com.tw http://www.zyxel.com http://www.zyxel.com.tw http://www.zygate.com.tw	<b>North America</b> ZyXEL Communications Inc. Tel: +1-714-632-0882 Fax: +1-714-632-0858 Email: sales@zyxel.com http://www.zyxel.com	<b>Germany</b> ZyXEL Deutschland GmbH. Tel: +49 2405 6909 0 Fax: +49 2405 6909 99 Email: sales@zyxel.de http://www.zyxel.de	<b>Denmark</b> ZyXEL Communications A/S Tel: +45 39 55 07 00 Fax: +45 39 55 07 07 Email: sales@zyxel.dk http://www.zyxel.dk	<b>Norway</b> ZyXEL Communications A/S Tel: +47 22 80 61 80 Fax: +47 22 80 61 81 Email: sales@zyxel.no http://www.zyxel.no	<b>Sweden</b> ZyXEL Communications A/S Tel: +46 31 744 7700 Fax: +46 31 744 7701 Email: sales@zyxel.se http://www.zyxel.se	<b>Finland</b> ZyXEL Communications Oy Tel: +358-9-4780 8400 Fax: +358-9-4780 8448 Email: sales@zyxel.fi
--	---	--	--	---	---	--