

segmentSeq: methods for identifying small RNA loci from high-throughput sequencing data

Thomas J. Hardcastle

November 8, 2014

1 Introduction

High-throughput sequencing technologies allow the production of large volumes of short sequences, which can be aligned to the genome to create a set of *matches* to the genome. By looking for regions of the genome which to which there are high densities of matches, we can infer a segmentation of the genome into regions of biological significance. The methods we propose allows the simultaneous segmentation of data from multiple samples, taking into account replicate data, in order to create a consensus segmentation. This has obvious applications in a number of classes of sequencing experiments, particularly in the discovery of small RNA loci and novel mRNA transcriptome discovery.

We approach the problem by considering a large set of potential *segments* upon the genome and counting the number of tags that match to that segment in multiple sequencing experiments (that may or may not contain replication). We then adapt the empirical Bayesian methods implemented in the `baySeq` package [1] to establish, for a given segment, the likelihood that the count data in that segment is similar to background levels, or that it is similar to the regions to the left or right of that segment. We then rank all the potential segments in order of increasing likelihood of similarity and reject those segments for which there is a high likelihood of similarity with the background or the regions to the left or right of the segment. This gives us a large list of overlapping segments. We reduce this list to identify non-overlapping loci by choosing, for a set of overlapping segments, the segment which has the lowest likelihood of similarity with either background or the regions to the left or right of that segment and rejecting all other segments that overlap with this segment. For fuller details of the method, see Hardcastle *et al.* [2].

2 Preparation

We begin by loading the `segmentSeq` package.

```
> library(segmentSeq)
```

Note that because the experiments that `segmentSeq` is designed to analyse are usually massive, we should use (if possible) parallel processing as implemented by the `parallel` package. If using this approach, we need to begin by define a *cluster*. The following command will use eight processors on a single machine; see the help page for 'makeCluster' for more information. If we don't want to parallelise, we can proceed anyway with a `NULL` cluster.

```
> if(require("parallel"))
+ {
+   numCores <- min(8, detectCores())
+   cl <- makeCluster(numCores)
+ } else {
+   cl <- NULL
+ }
```

The `readGeneric` function is able to read in tab-delimited files which have appropriate column names, and create an `alignmentData` object. Alternatively, if the appropriate column names are not present, we can specify which columns to use for the data. In either case, to use this function we pass a character vector of files, together with information on which data are to be treated as replicates to the function. We also need to define the lengths of

the chromosome and specify the chromosome names as a character. The data here, drawn from text files in the 'data' directory of the segmentSeq package are taken from the first million bases of an alignment to chromosome 1 and the first five hundred thousand bases of an alignment to chromosome 2 of *Arabidopsis thaliana* in a sequencing experiment where libraries 'SL9' and 'SL10' are replicates, as are 'SL26' and 'SL32'. Libraries 'SL9' and 'SL10' are sequenced from an Argonaute 6 IP, while 'SL26' and 'SL32' are an Argonaute 4 IP.

A similar function, readBAM performs the same operation on files in the BAM format. Please consult the help page for further details.

```
> chrlens <- c(1e6, 2e5)
> datadir <- system.file("extdata", package = "segmentSeq")
> libfiles <- c("SL9.txt", "SL10.txt", "SL26.txt", "SL32.txt")
> libnames <- c("SL9", "SL10", "SL26", "SL32")
> replicates <- c("AG06", "AG06", "AG04", "AG04")
> aD <- readGeneric(files = libfiles, dir = datadir,
+                   replicates = replicates, libnames = libnames,
+                   chrs = c(">Chr1", ">Chr2"), chrlens = chrlens,
+                   polyLength = 10, header = TRUE, gap = 200)
> aD
```

An object of class "alignmentData"
13765 rows and 4 columns

Slot "libnames":
[1] "SL9" "SL10" "SL26" "SL32"

Slot "replicates":
[1] AG06 AG06 AG04 AG04
Levels: AG04 AG06

Slot "alignments":
GRanges object with 13765 ranges and 2 metadata columns:

	seqnames	ranges	strand	tag	multireads
	<Rle>	<IRanges>	<Rle>	<character>	<numeric>
[1]	>Chr1	[265, 284]	-	AAATGAAGATAAACCATCCA	1
[2]	>Chr1	[405, 427]	-	AAGGAGTAAGAATGACAATAAAT	1
[3]	>Chr1	[406, 420]	-	AAGAATGACAATAAAA	1
[4]	>Chr1	[600, 623]	+	AAGGATTGGTGGTTTGAAGACACA	1
[5]	>Chr1	[665, 688]	+	ATCCTTGTAGCACACATTTGGCA	1
...
[13761]	>Chr2	[179972, 179993]	+	ATGAATGGCTCTCTCTAGCGGA	1
[13762]	>Chr2	[179978, 180000]	-	GAGATTCTCCGCTAGAGAGAGCC	1
[13763]	>Chr2	[179999, 180022]	-	ATTAATATTAATTCATCGGGAAGA	1
[13764]	>Chr2	[180002, 180022]	-	ATTAATATTAATTCATCGGGA	1
[13765]	>Chr2	[180014, 180037]	+	AATATTAATGTATTTGTGGAAAA	1

seqinfo: 2 sequences from an unspecified genome

Slot "data":
Matrix with 13765 rows.

	SL9	SL10	SL26	SL32
1	1	0	0	0
2	0	0	0	2
3	0	1	0	0
4	0	1	0	0
5	7	1	0	0
...
13761	2	7	0	0
13762	0	1	0	0
13763	0	1	0	0

```
13764  0    1    0    0
13765  1    0    0    0
```

```
Slot "libsizes":
[1] 4447 6531 9666 6675
```

Next, we process this alignmentData object to produce a segData object. This segData object contains a set of potential segments on the genome defined by the start and end points of regions of overlapping alignments in the alignmentData object. It then evaluates the number of tags that hit in each of these segments.

```
> sD <- processAD(aD, gap = 100, c1 = c1)
> sD
```

```
An object of class "segData"
14444 rows and 4 columns
```

```
Slot "replicates":
[1] AG06 AG06 AG04 AG04
Levels: AG04 AG06
```

```
Slot "coordinates":
GRanges object with 14444 ranges and 0 metadata columns:
```

	seqnames	ranges	strand
	<Rle>	<IRanges>	<Rle>
[1]	>Chr1	[265, 284]	*
[2]	>Chr1	[405, 427]	*
[3]	>Chr1	[600, 623]	*
[4]	>Chr1	[600, 688]	*
[5]	>Chr1	[600, 830]	*
...
[14440]	>Chr2	[179708, 179872]	*
[14441]	>Chr2	[179708, 180037]	*
[14442]	>Chr2	[179738, 179872]	*
[14443]	>Chr2	[179738, 180037]	*
[14444]	>Chr2	[179923, 180037]	*

```
-----
seqinfo: 2 sequences from an unspecified genome
```

```
Slot "locLikelihoods" (stored on log scale):
Matrix with 0 rows.
<0 x 0 matrix>
```

```
Slot "data":
Matrix with 0 rows. Matrix with 0 rows.
SL9 SL10 SL26 SL32
```

```
Slot "libsizes":
[1] 4447 6531 9666 6675
```

We can now construct a segment map from these potential segments.

Segmentation by heuristic methods

A fast method of segmentation can be achieved by exploiting the bimodality of the densities of small RNAs in the potential segments. In this approach, we assign each potential segment to one of two clusters for each replicate group, either as a segment or a null based on the density of sequence tags within that segment. We then combine these clusterings for each replicate group to gain a consensus segmentation map.

```
> hS <- heuristicSeg(sD = sD, aD = aD, RKPM = 1000, largeness = 1e8, getLikes = TRUE, c1 = c1)
```

.....

Segmentation by empirical Bayesian methods

A more refined approach to the problem uses an existing segment map (or, if not provided, a segment map defined by the `hS` function) to acquire empirical distributions on the density of sequence tags within a segment. We can then estimate posterior likelihoods for each potential segment as being either a true segment or a null. We then identify all potential segments in the with a posterior likelihood of being a segment greater than some value '`lociCutoff`' and containing no subregion with a posterior likelihood of being a null greater than '`nullCutoff`'. We then greedily select the longest segments satisfying these criteria that do not overlap with any other such segments in defining our segmentation map.

```
> classSegs <- classifySeg(sD = sD, aD = aD, cD = hS,
+                          subRegion = NULL, getLikes = TRUE,
+                          lociCutoff = 0.9, nullCutoff = 0.9, cl = cl)
```

.....

```
> classSegs
```

GRanges object with 254 ranges and 0 metadata columns:

	seqnames	ranges	strand
	<Rle>	<IRanges>	<Rle>
[1]	>Chr1	[1, 599]	*
[2]	>Chr1	[600, 967]	*
[3]	>Chr1	[968, 17054]	*
[4]	>Chr1	[17055, 18728]	*
[5]	>Chr1	[18729, 27656]	*
...
[250]	>Chr2	[169231, 178343]	*
[251]	>Chr2	[178344, 178636]	*
[252]	>Chr2	[178637, 179707]	*
[253]	>Chr2	[179708, 180037]	*
[254]	>Chr2	[180038, 200000]	*

seqinfo: 2 sequences from an unspecified genome

An object of class "lociData"

254 rows and 4 columns

Slot "replicates"

AG06 AG06 AG04 AG04

Slot "groups":

[[1]]

[1] AG06 AG06 AG04 AG04

Levels: AG04 AG06

Slot "data":

	AG06.1	AG06.2	AG04.1	AG04.2
[1,]	1	1	0	2
[2,]	54	46	65	83
[3,]	5	3	0	0
[4,]	758	705	1552	1648
[5,]	0	3	0	0

249 more rows...

Slot "annotation":

data frame with 0 columns and 254 rows

Slot "locLikelihoods" (stored on log scale):

Matrix with 254 rows.

	AG04	AG06
1	0.21741	0.09099
2	0.92039	0.97048
3	0.032056	0.036998
4	0.95732	0.99729
5	0.034007	0.046542
...
250	0.2807	0.058138
251	0.92044	0.97974
252	0.049102	0.056604
253	0.93886	0.97288
254	0.031777	0.024197

Expected number of loci in each replicate group

	AG04	AG06
	107.9827	134.8107

By one of these methods, we finally acquire an annotated lociData object, with the annotations describing the co-ordinates of each segment.

We can use this lociData object, in combination with the alignmentData object, to plot the segmented genome.

```
> par(mfrow = c(2,1), mar = c(2,6,2,2))
> plotGenome(aD, hS, chr = ">Chr1", limits = c(1, 1e5),
+           showNumber = FALSE, cap = 50)
> plotGenome(aD, classSegs, chr = ">Chr1", limits = c(1, 1e5),
+           showNumber = FALSE, cap = 50)
```

Given the calculated likelihoods, we can filter the segmented genome by controlling on likelihood, false discovery rate, or familywise error rate

```
> loci <- selectLoci(classSegs, FDR = 0.05)
> loci
```

GRanges object with 106 ranges and 0 metadata columns:

	seqnames	ranges	strand
	<Rle>	<IRanges>	<Rle>
[1]	>Chr1	[600, 967]	*
[2]	>Chr1	[17055, 18728]	*
[3]	>Chr1	[44710, 44870]	*
[4]	>Chr1	[76799, 76890]	*
[5]	>Chr1	[77115, 77523]	*
...
[102]	>Chr2	[152150, 152173]	*
[103]	>Chr2	[152768, 152829]	*
[104]	>Chr2	[169196, 169230]	*
[105]	>Chr2	[178344, 178636]	*
[106]	>Chr2	[179708, 180037]	*

seqinfo: 2 sequences from an unspecified genome

An object of class "lociData"

106 rows and 4 columns

Slot "replicates"

AG06 AG06 AG04 AG04

Slot "groups":

[[1]]

[1] AG06 AG06 AG04 AG04

Levels: AG04 AG06




Figure 1: The segmented genome (first 10^5 bases of chromosome 1.

Slot "data":

	AG06.1	AG06.2	AG04.1	AG04.2
[1,]	54	46	65	83
[2,]	758	705	1552	1648
[3,]	73	58	47	21
[4,]	6	19	0	0
[5,]	176	148	275	131

101 more rows...

Slot "annotation":

data frame with 0 columns and 106 rows

Slot "locLikelihoods" (stored on log scale):

Matrix with 106 rows.

	AG04	AG06
1	0.92039	0.97048
2	0.95732	0.99729
3	0.92525	0.99607
4	0.08985	0.9687
5	0.94877	0.9961

```
...      ...      ...
102 0.12281 0.96724
103 0.93782 0.95487
104 0.11207 0.98899
105 0.92044 0.97974
106 0.93886 0.97288
```

Expected number of loci in each replicate group

```
      AG04      AG06
74.65911 103.20513
```

This lociData object can now be examined for differential expression with the baySeq package.

Finally, to be a good citizen, we stop the cluster we started earlier:

```
> if(!is.null(cl))
+   stopCluster(cl)
```

Session Info

```
> sessionInfo()
```

R version 3.1.2 (2014-10-31)

Platform: i386-w64-mingw32/i386 (32-bit)

locale:

```
[1] LC_COLLATE=C                      LC_CTYPE=English_United States.1252
[3] LC_MONETARY=English_United States.1252 LC_NUMERIC=C
[5] LC_TIME=English_United States.1252
```

attached base packages:

```
[1] stats4      parallel    stats      graphics  grDevices  utils      datasets  methods
[9] base
```

other attached packages:

```
[1] segmentSeq_2.0.1      ShortRead_1.24.0      GenomicAlignments_1.2.1
[4] Rsamtools_1.18.1      Biostrings_2.34.0      XVector_0.6.0
[7] BiocParallel_1.0.0     baySeq_2.0.50          abind_1.4-0
[10] GenomicRanges_1.18.1  GenomeInfoDb_1.2.2     IRanges_2.0.0
[13] S4Vectors_0.4.0       BiocGenerics_0.12.0
```

loaded via a namespace (and not attached):

```
[1] BBmisc_1.8           BatchJobs_1.5          Biobase_2.26.0         BiocStyle_1.4.1
[5] DBI_0.3.1            RColorBrewer_1.0-5     RSQlite_1.0.0          base64enc_0.1-2
[9] bitops_1.0-6         brew_1.0-6             checkmate_1.5.0        codetools_0.2-9
[13] digest_0.6.4         fail_1.2               foreach_1.4.2          grid_3.1.2
[17] hwriter_1.3.2        iterators_1.0.7        lattice_0.20-29        latticeExtra_0.6-26
[21] sendmailR_1.2-1      stringr_0.6.2          tools_3.1.2            zlibbioc_1.12.0
```

References

- [1] Thomas J. Hardcastle and Krystyna A. Kelly. *baySeq: Empirical Bayesian Methods For Identifying Differential Expression In Sequence Count Data*. BMC Bioinformatics (2010).
- [2] Thomas J. Hardcastle and Krystyna A. Kelly and David C. Baulcombe. *Identifying small RNA loci from high-throughput sequencing data*. Bioinformatics (2012).