

MIGSA: Getting pbcmc datasets

Juan C Rodriguez

CONICET

Universidad Católica de Córdoba

Universidad Nacional de Córdoba

Cristóbal Fresno

Instituto Nacional de Medicina Genómica

Andrea S Llera

CONICET

Fundación Instituto Leloir

Elmer A Fernández

CONICET

Universidad Católica de Córdoba

Universidad Nacional de Córdoba

Abstract

In this vignette we are going to show how we got the RData *pbcmcData.RData* which can be loaded via the **MIGSAdata** package using `data(pbcmcData)`.

Keywords: singular enrichment analysis, over representation analysis, gene set enrichment analysis, functional class scoring, big omics data.

1. Getting the data

Following we give the used code to download this data and their PAM50 subtypes.

```
> library(limma);
> library(pbcmc);
> # datasets included in BioConductor repository
> libNames <- c("mainz", "nki", "transbig", "unt", "upp", "vdx");
> # let's load them!
> pbcmcData <- lapply(libNames, function(actLibName) {
+   print(actLibName);
+
+   # the pbcmc package provides an easy way to download and classify them
+   actLib <- loadBCDataset(Class=PAM50, libname=actLibName, verbose=FALSE);
+   actLibFilt <- filtrate(actLib, verbose=FALSE);
+   actLibFilt <- classify(actLibFilt, std="none", verbose=FALSE);
+   actSubtypes <- classification(actLibFilt)$subtype;
+
+   # get the expression matrix and the annotation
+   actExprs <- exprs(actLib);
+   actAnnot <- annotation(actLib);
+ })
```

```

+   # we recommend working allways with Entrez IDs, let's match them with
+   # expression matrix rownames (and modify them)
+   if (all(actAnnot$probe == rownames(actExprs))) {
+       actExprs <- actExprs[!is.na(actAnnot$EntrezGene.ID),];
+       actAnnot <- actAnnot[!is.na(actAnnot$EntrezGene.ID),];
+       rownames(actExprs) <- as.character(actAnnot$EntrezGene.ID);
+   } else {
+       matchedEntrez <- match(rownames(actExprs), actAnnot$probe);
+       # all(rownames(actExprs) %in% actAnnot$probe == !is.na(matchedEntrez));
+
+       stopifnot(all(
+           actAnnot$probe[!is.na(matchedEntrez)] ==
+           rownames(actExprs)[!is.na(matchedEntrez)]));
+
+       actExprs <- actExprs[!is.na(matchedEntrez),];
+       actAnnot <- actAnnot[!is.na(matchedEntrez),];
+       stopifnot(all(actAnnot$probe == rownames(actExprs)));
+       actExprs <- actExprs[!is.na(actAnnot$EntrezGene.ID),];
+       actAnnot <- actAnnot[!is.na(actAnnot$EntrezGene.ID),];
+       rownames(actExprs) <- as.character(actAnnot$EntrezGene.ID);
+   }
+
+   # average repeated genes expression
+   actExprs <- avereps(actExprs);
+
+   stopifnot(all(colnames(actExprs) == names(actSubtypes)));
+   # filtrate only these two conditions
+   actExprs <- actExprs[, actSubtypes %in% c("Basal", "LumA")];
+   actSubtypes <- as.character(
+       actSubtypes[actSubtypes %in% c("Basal", "LumA")]);
+
+   return(list(geneExpr=actExprs, subtypes=actSubtypes));
+ })
> names(pbcmcData) <- libNames;

```

And let's check it is the same data.

```

> # save the just created pbcmcData to newPbcmcData
> newPbcmcData <- pbcmcData;
> library(MIGSAdata);
> # and load the MIGSAdata one.
> data(pbcmcData);
> all.equal(newPbcmcData, pbcmcData);

```

Session Info

```
> sessionInfo()
```

```
R version 3.6.0 (2019-04-26)
Platform: x86_64-w64-mingw32/x64 (64-bit)
Running under: Windows Server 2012 R2 x64 (build 9600)
```

```
Matrix products: default
```

```
locale:
```

```
[1] LC_COLLATE=C
[2] LC_CTYPE=English_United States.1252
[3] LC_MONETARY=English_United States.1252
[4] LC_NUMERIC=C
[5] LC_TIME=English_United States.1252
```

```
attached base packages:
```

```
[1] stats4      parallel  stats      graphics  grDevices  utils      datasets
[8] methods     base
```

```
other attached packages:
```

```
[1] edgeR_3.26.0      MIGSAdat_1.7.0      MIGSA_1.8.0
[4] mGSZ_1.0          ismev_1.42          mgcv_1.8-28
[7] nlme_3.1-139      MASS_7.3-51.4       limma_3.40.0
[10] GSA_1.03.1        BiocParallel_1.18.0 GSEABase_1.46.0
[13] graph_1.62.0      annotate_1.62.0      XML_3.98-1.19
[16] AnnotationDbi_1.46.0 IRanges_2.18.0      S4Vectors_0.22.0
[19] Biobase_2.44.0    BiocGenerics_0.30.0
```

```
loaded via a namespace (and not attached):
```

```
[1] gg dendro_0.1-20      bit64_0.9-7          splines_3.6.0
[4] assertthat_0.2.1     RBGL_1.60.0          blob_1.1.1
[7] Category_2.50.0      pillar_1.3.1         RSQLite_2.1.1
[10] lattice_0.20-38      glue_1.3.1           digest_0.6.18
[13] colorspace_1.4-1     Matrix_1.2-17        plyr_1.8.4
[16] pkgconfig_2.0.2      genefilter_1.66.0    purrr_0.3.2
[19] xtable_1.8-4         GO.db_3.8.2          scales_1.0.0
[22] snow_0.4-3           tibble_2.1.1         ggplot2_3.1.1
[25] lazyeval_0.2.2       survival_2.44-1.1    RJSONIO_1.3-1.1
[28] magrittr_1.5         crayon_1.3.4         memoise_1.1.0
[31] GOstats_2.50.0       vegan_2.5-4          tools_3.6.0
[34] data.table_1.12.2    org.Hs.eg.db_3.8.2   formatR_1.6
[37] matrixStats_0.54.0   stringr_1.4.0        munsell_0.5.0
[40] locfit_1.5-9.1       cluster_2.0.9        lambda.r_1.2.3
[43] compiler_3.6.0       rlang_0.3.4          futile.logger_1.4.3
[46] grid_3.6.0           RCurl_1.95-4.12      AnnotationForge_1.26.0
[49] labeling_0.3         bitops_1.0-6         gtable_0.3.0
[52] DBI_1.0.0            reshape2_1.4.3       R6_2.4.0
```

[55]	dplyr_0.8.0.1	bit_1.1-14	futile.options_1.0.1
[58]	permute_0.9-5	Rgraphviz_2.28.0	stringi_1.4.3
[61]	Rcpp_1.0.1	tidyselect_0.2.5	

Affiliation:

Juan C Rodriguez & Elmer A Fernández

Bioscience Data Mining Group

Facultad de Ingeniería

Universidad Católica de Córdoba - CONICET

X5016DHK Córdoba, Argentina

E-mail: jcrodriguez@bdmg.com.ar, efernandez@bdmg.com.ar

URL: <http://www.bdmg.com.ar/>