

Package ‘Bchron’

December 12, 2025

Type Package

Title Age-Depth Radiocarbon Modelling

Version 4.7.8

Date 2025-12-11

URL <https://andrewcparnell.github.io/Bchron/>

BugReports <https://github.com/andrewcparnell/Bchron/issues>

Depends R (>= 4.1.0),

Imports utils, MASS, coda, mclust, ggplot2, ggridges, magrittr, purrr,
ggforce, dplyr, scales, stringr, checkmate, methods

Encoding UTF-8

Description Enables quick calibration of radiocarbon dates under various calibration curves (including user generated ones); age-depth modelling as per the algorithm of Haslett and Parnell (2008) <[DOI:10.1111/j.1467-9876.2008.00623.x](https://doi.org/10.1111/j.1467-9876.2008.00623.x)>; Relative sea level rate estimation incorporating time uncertainty in polynomial regression models (Parnell and Gehrels 2015) <[DOI:10.1002/9781118452547.ch32](https://doi.org/10.1002/9781118452547.ch32)>; non-parametric phase modelling via Gaussian mixtures as a means to determine the activity of a site (and as an alternative to the 'Oxcal' function SUM(); currently unpublished), and reverse calibration of dates from calibrated into 14C years (also unpublished).

License GPL (>= 2)

Suggests knitr, testthat (>= 3.0.0), rmarkdown, covr

VignetteBuilder knitr, rmarkdown

NeedsCompilation yes

RoxygenNote 7.3.3

Language en-US

Config/testthat/edition 3

Author Andrew Parnell [cre, aut],
Nathan McJames [ctb],
Bruna Wundervald [ctb],
Keefe Murphy [ctb],
Mateus Maia [ctb],

Amin Shoari Nejad [ctb],
Yong Chen Goh [ctb]

Maintainer Andrew Parnell <Andrew.Parnell11@ucd.ie>

Repository CRAN

Date/Publication 2025-12-12 16:10:02 UTC

Contents

Bchron	3
BchronCalibrate	4
BchronCheck	6
BchronDensity	9
BchronDensityFast	11
Bchronology	12
BchronRSL	16
choosePositions	18
coreInfluence	20
createCalCurve	22
dateInfluence	23
Glendalough	25
hdr	25
intcal13	26
intcal20	27
marine13	27
marine20	28
normal	28
plot.BchronCalibratedDates	29
plot.BchronDensityRun	30
plot.BchronDensityRunFast	31
plot.BchronologyRun	32
plot.BchronRSLRun	33
predict.BchronologyRun	34
sampleAges	35
shcal13	36
shcal20	37
Sluggan	37
summary.BchronCalibratedDates	38
summary.BchronDensityRun	39
summary.BchronologyRun	39
summary.BchronRSLRun	40
TestChronData	41
TestRSLData	42
unCalibrate	43

Index	45
--------------	-----------

Bchron*Bchron: Radiocarbon dating, age-depth modelling, relative sea level rate estimation, and non-parametric phase modelling*

Description

This package enables quick calibration of radiocarbon dates under various calibration curves (including user generated ones); Age-depth modelling as per the algorithm of Haslett and Parnell (2008); Relative sea level rate estimation incorporating time uncertainty in polynomial regression models; and non-parametric phase modelling via Gaussian mixtures as a means to determine the activity of a site (and as an alternative to the Oxcal function SUM)

Bchron functions

The most important functions are [BchronCalibrate](#) to calibrate radiocarbon (and non-radiocarbon) dates, [Bchronology](#) for the age-depth model of Haslett and Parnell (2008), [BchronRSL](#) to get rate estimates for relative sea level data, [BchronDensity](#) and [BchronDensityFast](#) for non-parametric phase modelling of age data. See the help files for these functions for examples. See the vignette for more complete documentation

Author(s)

Maintainer: Andrew Parnell <Andrew.Parnell11@ucd.ie>

Other contributors:

- Nathan McJames [contributor]
- Bruna Wundervald [contributor]
- Keefe Murphy [contributor]
- Mateus Maia [contributor]
- Amin Shoari Nejad [contributor]
- Yong Chen Goh [contributor]

See Also

Useful links:

- <https://andrewcparnell.github.io/Bchron/>
- Report bugs at <https://github.com/andrewcparnell/Bchron/issues>

BchronCalibrate	<i>Fast radiocarbon calibration</i>
-----------------	-------------------------------------

Description

A fast function for calibrating large numbers of radiocarbon dates involving multiple calibration curves

Usage

```
BchronCalibrate(
  ages,
  ageSds,
  calCurves = rep("intcal20", length(ages)),
  ids = NULL,
  positions = NULL,
  pathToCalCurves = system.file("data", package = "Bchron"),
  allowOutside = FALSE,
  eps = 1e-05,
  dfs = rep(100, length(ages))
)
```

Arguments

ages	A vector of ages provided in years before 1950.
ageSds	A vector of 1-sigma values for the ages given above
calCurves	A vector of values containing either intcal20, shcal20, marine20, or normal (older calibration curves are supposed such as intcal13). Should be the same length the number of ages supplied. Non-standard calibration curves can be used provided they are supplied in the same format as those previously mentioned and are placed in the same directory. Normal indicates a normally-distributed (non-14C) age.
ids	ID names for each age
positions	Position values (e.g. depths) for each age. In the case of layers of non-zero thickness, this should be the middle value of the slice
pathToCalCurves	File path to where the calibration curves are located. Defaults to the system directory where the 3 standard calibration curves are stored.
allowOutside	Whether to allow calibrations to run outside the range of the calibration curve. By default this is turned off as calibrations outside of the range of the calibration curve can cause severe issues with probability ranges of calibrated dates
eps	Cut-off point for density calculation. A value of $\text{eps} > 0$ removes ages from the output which have negligible probability density
dfs	Degrees-of-freedom values for the t-distribution associated with the calibration calculation. A large value indicates Gaussian distributions assumed for the 14C ages

Details

This function provides a direct numerical integration strategy for computing calibrated radiocarbon ages. The steps for each 14C age are approximately as follows: 1) Create a grid of ages covering the range of the calibration curve 2) Calculate the probability of each age according to the 14C age, the standard deviation supplied and the calibration curve 3) Normalise the probabilities so that they sum to 1 4) Remove any probabilities that are less than the value given for eps Multiple calibration curves can be specified so that each 14C age can have a different curve. For ages that are not 14C, use the 'normal' calibration curve which treats the ages as normally distributed with given standard deviation

Value

A list of lists where each element corresponds to a single age. Each element contains:

ages The original age supplied
ageSds The original age standard deviation supplied
positions The position of the age (usually the depth)
calCurves The calibration curve used for that age
ageGrid A grid of age values over which the density was created
densities A vector of probability values indicating the probability value for each element in ageGrid
ageLab The label given to the age variable
positionLab The label given to the position variable

See Also

[Bchronology](#), [BchronRSL](#), [BchronDensity](#), [BchronDensityFast](#), [createCalCurve](#)

Examples

```
# Calibrate a single age
ages1 <- BchronCalibrate(
  ages = 11553,
  ageSds = 230,
  calCurves = "intcal20",
  ids = "Date-1"
)
summary(ages1)
plot(ages1)

# Or plot with Calibration curve
plot(ages1, includeCal = TRUE)

# Calibrate multiple ages with different calibration curves
ages2 <- BchronCalibrate(
  ages = c(3445, 11553, 7456),
  ageSds = c(50, 230, 110),
  calCurves = c("intcal20", "intcal20", "shcal20")
)
```

```
summary(ages2)
plot(ages2)

# Calibrate multiple ages with multiple calibration curves and including depth
ages3 <- BchronCalibrate(
  ages = c(3445, 11553),
  ageSds = c(50, 230),
  positions = c(100, 150),
  calCurves = c("intcal20", "normal")
)
summary(ages3)
plot(ages3, withPositions = TRUE)
```

BchronCheck

Check data for input into BchronCalibrate or Bchronology

Description

Function to be used for checking the data formats in [BchronCalibrate](#) and [Bchronology](#). Mostly to be used internally to avoid Bchron running into problems with bad data specifications, but might also be useful for

Usage

```
BchronCheck(
  ages,
  ageSds,
  positions = NULL,
  pathToCalCurves = NULL,
  calCurves = NULL,
  positionThicknesses = NULL,
  ids = NULL,
  outlierProbs = NULL,
  predictPositions = NULL,
  artificialThickness = NULL,
  allowOutside = NULL,
  iterations = NULL,
  thetaStart = NULL,
  burn = NULL,
  thin = NULL,
  extractDate = NULL,
  maxExtrap = NULL,
  thetaMhSd = NULL,
  muMhSd = NULL,
  psiMhSd = NULL,
  ageScaleVal = NULL,
  positionEps = NULL,
  positionNormalise = NULL,
```

```

    eps = NULL,
    dfs = NULL,
    type = c("BchronCalibrate", "Bchronology")
  )

```

Arguments

ages	A vector of ages provided in years before 1950.
ageSds	A vector of 1-sigma values for the ages given above
positions	Position values (e.g. depths) for each age. In the case of layers of non-zero thickness, this should be the middle value of the slice
pathToCalCurves	File path to where the calibration curves are located. Defaults to the system directory where the 3 standard calibration curves are stored.
calCurves	A vector of values containing either <code>intcal20</code> , <code>shcal20</code> , <code>marine20</code> , or <code>normal</code> (older calibration curves are supposed such as <code>intcal13</code>). Should be the same length the number of ages supplied. Non-standard calibration curves can be used provided they are supplied in the same format as those previously mentioned and are placed in the same directory. Normal indicates a normally-distributed (non-14C) age.
positionThicknesses	Thickness values for each of the positions. The thickness value should be the full thickness value of the slice. By default set to zero.
ids	ID names for each age
outlierProbs	A vector of prior outlier probabilities, one for each age. Defaults to 0.01
predictPositions	A vector of positions (e.g. depths) at which predicted age values are required. Defaults to a sequence of length 100 from the top position to the bottom position
artificialThickness	Amount to add to the thickness values in the case of equal positions with no <code>positionThicknesses</code> . Bchron may fail if <code>positionThicknesses</code> are zero and some positions are repeated. This value is added on to the zero thicknesses (only in the case of repeated positions) to stop this failure.
allowOutside	Whether to allow calibrations to run outside the range of the calibration curve. By default this is turned off as calibrations outside of the range of the calibration curve can cause severe issues with probability ranges of calibrated dates
iterations	The number of iterations to run the procedure for
thetaStart	A set of starting values for the calendar ages estimated by Bchron. If NULL uses a function to estimate the ages. These should be in the same units as the posterior ages required. See example below for usage.
burn	The number of starting iterations to discard
thin	The step size for every iteration to keep beyond the burn-in
extractDate	The top age of the core. Used for extrapolation purposes so that no extrapolated ages go beyond the top age of the core. Defaults to the current year

<code>maxExtrap</code>	The maximum number of extrapolations to perform before giving up and setting the predicted ages to NA. Useful for when large amounts of extrapolation are required, i.e. some of the <code>predictPositions</code> are a long way from the dated positions
<code>thetaMhSd</code>	The Metropolis-Hastings standard deviation for the age parameters
<code>muMhSd</code>	The Metropolis-Hastings standard deviation for the Compound Poisson-Gamma mean
<code>psiMhSd</code>	The Metropolis-Hastings standard deviation for the Compound Poisson-Gamma scale
<code>ageScaleVal</code>	A scale value for the ages. Bchronology works best when the ages are scaled to be approximately between 0 and 100. The default value is thus 1000 for ages given in years.
<code>positionEps</code>	A small value used to check whether simulated positions are far enough apart to avoid numerical underflow errors. If errors occur in model runs (e.g. missing value where TRUE/FALSE needed increase this value)
<code>positionNormalise</code>	Whether to normalise the position values. Bchronology works best when the positions are normalised to be between 0 and 1 The default value is TRUE
<code>eps</code>	Cut-off point for density calculation. A value of <code>eps>0</code> removes ages from the output which have negligible probability density
<code>dfs</code>	Degrees-of-freedom values for the t-distribution associated with the calibration calculation. A large value indicates Gaussian distributions assumed for the 14C ages
<code>type</code>	Whether this function has been called to check parameters for calibration purposes (<code>BchronCalibrate</code>) or chronology purposes (<code>Bchronology</code>)

Value

This function returns nothing other than a message.

Examples

```
data(Glendalough)

# Check the Glendalough data are in the right format
with(
  Glendalough,
  BchronCheck(ages,
    ageSds,
    position,
    pathToCalCurves = system.file("data", package = "Bchron"),
    calCurves,
    type = "BchronCalibrate"
  )
)
```

BchronDensity	<i>Non-parametric phase model</i>
---------------	-----------------------------------

Description

This function runs a non-parametric phase model on 14C and non-14C ages via Gaussian Mixture density estimation

Usage

```
BchronDensity(
  ages,
  ageSds,
  calCurves,
  pathToCalCurves = system.file("data", package = "Bchron"),
  dfs = rep(100, length(ages)),
  numMix = 50,
  iterations = 10000,
  burn = 2000,
  thin = 8,
  updateAges = FALSE,
  store_density = TRUE
)
```

Arguments

ages	A vector of ages (most likely 14C)
ageSds	A vector of 1-sigma values for the ages given above
calCurves	A vector of values containing either intcal20, shcal20, marine20, or normal (older calibration curves such as intcal13 are also supported). Should be the same length the number of ages supplied. Non-standard calibration curves can be used provided they are supplied in the same format as those previously mentioned and are placed in the same directory. Normal indicates a normally-distributed (non-14C) age.
pathToCalCurves	File path to where the calibration curves are located. Defaults to the system directory where the 3 standard calibration curves are stored
dfs	Degrees-of-freedom values for the t-distribution associated with the calibration calculation. A large value indicates Gaussian distributions assumed for the 14C ages
numMix	The number of mixture components in the phase model. Might need to be increased if the data set is large and the phase behaviour is very complex
iterations	The number of iterations to run for
burn	The number of starting iterations to discard
thin	The step size of iterations to keep

<code>updateAges</code>	Whether or not to update ages as part of the MCMC run. Default is FALSE. Changing this to TRUE will improve performance but will fit a slightly invalid model
<code>store_density</code>	Whether or not to store the density and age grid. Useful for plotting the output in other packages

Details

This model places a Gaussian mixture prior distribution on the calibrated ages and so estimates the density of the overall set of radiocarbon ages. It is designed to be a probabilistic version of the Oxcal SUM command which takes calibrated ages and sums the probability distributions with the aim of estimating activity through age as a proxy.

Value

An object of class `BchronDensityRun` with the following elements:

theta The posterior samples of the restricted ages
p Posterior samples of the mixture proportions
mu Values of the means of each Gaussian mixture
calAges The calibrated ages from [BchronCalibrate](#)
G The number of mixture components. Equal to `numMix`
age_grid A grid of ages used for the final density estimate
density The density estimate based on the above age grid

See Also

[Bchronology](#), [BchronRSL](#), [BchronDensityFast](#) for a faster approximate version of this function

Examples

```
# Read in some data from Sluggan Moss
data(Sluggan)

# Run the model
SlugDens <- with(
  Sluggan,
  BchronDensity(
    ages = ages,
    ageSds = ageSds,
    calCurves = calCurves
  )
)

# plot it
plot(SlugDens)
```

BchronDensityFast	<i>Non-parametric phase model (faster version)</i>
-------------------	--

Description

This function runs a non-parametric phase model on 14C and non-14C ages via Gaussian Mixture density estimation through the mclust package

Usage

```
BchronDensityFast(
  ages,
  ageSds,
  calCurves,
  pathToCalCurves = system.file("data", package = "Bchron"),
  dfs = rep(100, length(ages)),
  samples = 2000,
  G = 30
)
```

Arguments

ages	A vector of ages (most likely 14C)
ageSds	A vector of 1-sigma values for the ages given above
calCurves	A vector of values containing either <code>intcal20</code> , <code>shcal20</code> , <code>marine20</code> , or <code>normal</code> (older calibration curves such as <code>intcal13</code> are also supported). Should be the same length the number of ages supplied. Non-standard calibration curves can be used provided they are supplied in the same format as those previously mentioned and are placed in the same directory. Normal indicates a normally-distributed (non-14C) age.
pathToCalCurves	File path to where the calibration curves are located. Defaults to the system directory where the 3 standard calibration curves are stored.
dfs	Degrees-of-freedom values for the t-distribution associated with the calibration calculation. A large value indicates Gaussian distributions assumed for the 14C ages
samples	Number of samples of calibrated dates required
G	Number of Gaussian mixture components

Details

This is a faster approximate version of [BchronDensity](#) that uses the [densityMclust](#) function to compute the Gaussian mixtures for a set of calibrated ages. The method is an approximation as it does not fit a fully Bayesian model as [BchronDensity](#) does. It is designed to be a probabilistic version of the Oxcal SUM command which takes calibrated ages and sums the probability distributions with the aim of estimating activity through age as a proxy.

Value

An object of class `BchronDensityRunFast` with the following components:

out The output from the run of `densityMclust` with the given number of mixture components

calAges The calibrated ages from the `BchronDensity` function

See Also

`Bchronology`, `BchronCalibrate`, `BchronRSL`, `BchronDensity` for a slower exact version of this function

Examples

```
# Read in some data from Sluggan Moss
data(Sluggan)

# Run the model
SlugDensFast <- with(
  Sluggan,
  BchronDensityFast(
    ages = ages,
    ageSds = ageSds,
    calCurves = calCurves
  )
)

# plot it
plot(SlugDensFast)
```

Bchronology

Runs the Compound Poisson-Gamma chronology model of Haslett and Parnell (2008)

Description

Fits a non-parametric chronology model to age/position data according to the Compound Poisson-Gamma model defined by Haslett and Parnell (2008) <DOI:10.1111/j.1467-9876.2008.00623.x>. This version uses a slightly modified Markov chain Monte Carlo fitting algorithm which aims to converge quicker and requires fewer iterations. It also a slightly modified procedure for identifying outliers

Usage

```
Bchronology(
  ages,
  ageSds,
  positions,
```

```

positionThicknesses = rep(0, length(ages)),
calCurves = rep("intcal20", length(ages)),
ids = NULL,
outlierProbs = rep(0.01, length(ages)),
predictPositions = seq(min(positions), max(positions), length = 100),
pathToCalCurves = system.file("data", package = "Bchron"),
artificialThickness = 0.01,
allowOutside = FALSE,
iterations = 10000,
burn = 2000,
thin = 8,
extractDate = 1950 - as.numeric(format(Sys.time(), "%Y")),
maxExtrap = 1000,
thetaStart = NULL,
thetaMhSd = 0.5,
muMhSd = 0.1,
psiMhSd = 0.1,
ageScaleVal = 1000,
positionEps = 1e-05,
positionNormalise = TRUE
)

```

Arguments

<code>ages</code>	A vector of ages provided in years before 1950.
<code>ageSds</code>	A vector of 1-sigma values for the ages given above
<code>positions</code>	Position values (e.g. depths) for each age. In the case of layers of non-zero thickness, this should be the middle value of the slice
<code>positionThicknesses</code>	Thickness values for each of the positions. The thickness value should be the full thickness value of the slice. By default set to zero.
<code>calCurves</code>	A vector of values containing either <code>intcal20</code> , <code>shcal20</code> , <code>marine20</code> , or <code>normal</code> (older calibration curves are supposed such as <code>intcal13</code>). Should be the same length the number of ages supplied. Non-standard calibration curves can be used provided they are supplied in the same format as those previously mentioned and are placed in the same directory. Normal indicates a normally-distributed (non-14C) age.
<code>ids</code>	ID names for each age
<code>outlierProbs</code>	A vector of prior outlier probabilities, one for each age. Defaults to 0.01
<code>predictPositions</code>	A vector of positions (e.g. depths) at which predicted age values are required. Defaults to a sequence of length 100 from the top position to the bottom position
<code>pathToCalCurves</code>	File path to where the calibration curves are located. Defaults to the system directory where the 3 standard calibration curves are stored.

<code>artificialThickness</code>	Amount to add to the thickness values in the case of equal positions with no <code>positionThicknesses</code> . Bchron may fail if <code>positionThicknesses</code> are zero and some positions are repeated. This value is added on to the zero thicknesses (only in the case of repeated positions) to stop this failure.
<code>allowOutside</code>	Whether to allow calibrations to run outside the range of the calibration curve. By default this is turned off as calibrations outside of the range of the calibration curve can cause severe issues with probability ranges of calibrated dates
<code>iterations</code>	The number of iterations to run the procedure for
<code>burn</code>	The number of starting iterations to discard
<code>thin</code>	The step size for every iteration to keep beyond the burn-in
<code>extractDate</code>	The top age of the core. Used for extrapolation purposes so that no extrapolated ages go beyond the top age of the core. Defaults to the current year
<code>maxExtrap</code>	The maximum number of extrapolations to perform before giving up and setting the predicted ages to NA. Useful for when large amounts of extrapolation are required, i.e. some of the <code>predictPositions</code> are a long way from the dated positions
<code>thetaStart</code>	A set of starting values for the calendar ages estimated by Bchron. If NULL uses a function to estimate the ages. These should be in the same units as the posterior ages required. See example below for usage.
<code>thetaMhSd</code>	The Metropolis-Hastings standard deviation for the age parameters
<code>muMhSd</code>	The Metropolis-Hastings standard deviation for the Compound Poisson-Gamma mean
<code>psiMhSd</code>	The Metropolis-Hastings standard deviation for the Compound Poisson-Gamma scale
<code>ageScaleVal</code>	A scale value for the ages. Bchronology works best when the ages are scaled to be approximately between 0 and 100. The default value is thus 1000 for ages given in years.
<code>positionEps</code>	A small value used to check whether simulated positions are far enough apart to avoid numerical underflow errors. If errors occur in model runs (e.g. missing value where TRUE/FALSE needed increase this value)
<code>positionNormalise</code>	Whether to normalise the position values. Bchronology works best when the positions are normalised to be between 0 and 1 The default value is TRUE

Details

The Bchronology function fits a compound Poisson-Gamma distribution to the increments between the dated levels. This involves a stochastic linear interpolation step where the age gaps are Gamma distributed, and the position gaps are Exponential. Radiocarbon and non-radiocarbon dates (including outliers) are updated within the function also by MCMC.

Value

A list of class BchronologyRun which include elements:

theta	The posterior estimated values of the ages
phi	The posterior estimated outlier values (1=outlier, 2=not outlier). The means of this parameter give the posterior estimated outlier probabilities
mu	The posterior values of the Compound Poisson-Gamma mean
psi	The posterior values of the Compound Poisson-Gamma scale
thetaPredict	The posterior estimated ages for each of the values in predictPosition
predictPositions	The positions at which estimated ages were required
calAges	The calibrated ages as output from BchronCalibrate
inputVals	All of the input values to the Bchronology run

References

Haslett, J., and Parnell, A. C. (2008). A simple monotone process with application to radiocarbon-dated depth chronologies. *Journal of the Royal Statistical Society, Series C*, 57, 399-418. DOI:10.1111/j.1467-9876.2008.00623.x Parnell, A. C., Haslett, J., Allen, J. R. M., Buck, C. E., and Huntley, B. (2008). A flexible approach to assessing synchronicity of past events using Bayesian reconstructions of sedimentation history. *Quaternary Science Reviews*, 27(19-20), 1872-1885. DOI:10.1016/j.quascirev.2008.07.009

See Also

[BchronCalibrate](#), [BchronRSL](#), [BchronDensity](#), [BchronDensityFast](#)

Examples

```
# Data from Glendalough
data(Glendalough)

# Run in Bchronology - all but first age uses intcal20
GlenOut <- with(
  Glendalough,
  Bchronology(
    ages = ages,
    ageSds = ageSds,
    calCurves = calCurves,
    positions = position,
    positionThicknesses = thickness,
    ids = id,
    predictPositions = seq(0, 1500, by = 10)
  )
)

# Summarise it a few different ways
summary(GlenOut) # Default is for quantiles of ages at predictPosition values
summary(GlenOut, type = "convergence") # Check model convergence
summary(GlenOut, type = "outliers") # Look at outlier probabilities

# Predict for some new positions
predictAges <- predict(GlenOut,
```

```

    newPositions = c(150, 725, 1500),
    newPositionThicknesses = c(5, 0, 20)
  )

  # Plot the output
  plot(GlenOut) +
    ggplot2::labs(
      title = "Glendalough",
      xlab = "Age (cal years BP)",
      ylab = "Depth (cm)"
    )

  # If you need to specify your own starting values
  startingAges <- c(0, 2000, 10000, 11000, 13000, 13500)
  GlenOut <- with(
    Glendalough,
    Bchronology(
      ages = ages,
      ageSds = ageSds,
      calCurves = calCurves,
      positions = position,
      positionThicknesses = thickness,
      ids = id,
      predictPositions = seq(0, 1500, by = 10),
      thetaStart = startingAges
    )
  )
)

```

BchronRSL

Relative sea level rate (RSL) estimation

Description

Relative sea level rate (RSL) estimation

Usage

```

BchronRSL(
  BchronologyRun,
  RSLmean,
  RSLsd,
  degree = 1,
  iterations = 10000,
  burn = 2000,
  thin = 8
)

```


Arguments

BchronologyRun	Output from a run of Bchronology
RSLmean	A vector of RSL mean estimates of the same length as the number of predictPositions given to the Bchronology function
RSLsd	A vector RSL standard deviations of the same length as the number of predictPositions given to the Bchronology function
degree	The degree of the polynomial regression: linear=1 (default), quadratic=2, etc. Supports up to degree 5, though this will depend on the data given
iterations	The number of MCMC iterations to run
burn	The number of starting iterations to discard
thin	The step size of iterations to discard

Details

This function fits an errors-in-variables regression model to relative sea level (RSL) data. An errors-in-variables regression model allows for uncertainty in the explanatory variable, here the age of sea level data point. The algorithm is more fully defined in the reference below

Value

An object of class BchronRSLRun with elements

BchronologyRun The output from the run of [Bchronology](#)

samples The posterior samples of the regression parameters

degree The degree of the polynomial regression

RSLmean The RSL mean values given to the function

RSLsd The RSL standard deviations as given to the function

const The mean of the predicted age values. Used to standardise the design matrix and avoid computational issues

References

Andrew C. Parnell and W. Roland Gehrels (2013) 'Using chronological models in late holocene sea level reconstructions from salt marsh sediments' In: I. Shennan, B.P. Horton, and A.J. Long (eds). Handbook of Sea Level Research. Chichester: Wiley

See Also

[BchronCalibrate](#), [Bchronology](#), [BchronDensity](#), [BchronDensityFast](#)

Examples

```
# Load in data
data(TestChronData)
data(TestRSLData)

# Run through Bchronology
RSLrun <- with(TestChronData, Bchronology(
  ages = ages,
  ageSds = ageSds,
  positions = position,
  positionThicknesses = thickness,
  ids = id,
  calCurves = calCurves,
  predictPositions = TestRSLData$Depth
))

# Now run through BchronRSL
RSLrun2 <- BchronRSL(RSLrun, RSLmean = TestRSLData$RSL, RSLsd = TestRSLData$Sigma, degree = 3)

# Summarise it
summary(RSLrun2)

# Plot it
plot(RSLrun2)
```

choosePositions	<i>Compute positions to date next which result in maximal decrease of chronological uncertainty</i>
-----------------	---

Description

This function finds, for a given current chronology, created via [Bchronology](#), which positions (depths) to date next. If $N = 1$ it just finds the position with the biggest uncertainty. If $N > 1$ it puts a date at the $N = 1$ position and re-runs [Bchronology](#) with the extra psuedo date. It uses the [unCalibrate](#) function with the un-calibrated age estimated at the median of the chronology and the sd as specified via the newSds argument. Other arguments specify the new thicknesses, calibration curves, and outlier probabilities for newly inserted psuedo-dates.

Usage

```
choosePositions(
  bchrRun,
  N = 1,
  newSds = 30,
  newThicknesses = 0,
  positions = bchrRun$predictPositions,
  newCalCurve = "intcal20",
```

```

    newOutlierProb = 0.05,
    level = 0.5,
    plot = TRUE,
    count = 1,
    linesAt = NULL
  )

```

Arguments

bchrRun	A run of the current chronology as output from Bchronology
N	The number of new positions required
newSds	The new standard deviations of the psuedo-added dates
newThicknesses	The new thicknesses of the psuedo-added dates
positions	The positions allowed to estimate the new positions to date. Defaults to the value of predictPositions from the Bchronology run
newCalCurve	The new calibration curve of the psuedo-added dates
newOutlierProb	The new outlier probabilities of the psuedo-added dates
level	The confidence level required for minimising the uncertainty. Defaults to 50%. (Note: this will be estimated more robustly than the 95% level)
plot	Whether to plot the chronologies as they are produced
count	Counter function (not for use other than by the function itself)
linesAt	Horizontal line positions (not for use other than by the function itself)

Value

Some plots and the positions to date next

See Also

[Bchronology](#) for the main function to create chronologies, [unCalibrate](#) for the ability to invert calendar dates for a given calibration curve.

Examples

```

data(Glendalough)
GlenOut <- Bchronology(
  ages = Glendalough$ages,
  ageSds = Glendalough$ageSds,
  calCurves = Glendalough$calCurves,
  positions = Glendalough$position,
  positionThicknesses = Glendalough$thickness,
  ids = Glendalough$id,
  predictPositions = seq(0, 1500, by = 10)
)

# Find out which two positions (depths) to date if we have room for two more dates
# Here going to choose 3 new positions to date

```

```

newPositions <- choosePositions(GlenOut, N = 3)
print(newPositions)

# Suppose you are only interested in dating the new depths at 500, 600, or 700 cm
newPositions2 <- choosePositions(GlenOut,
  N = 2,
  positions = seq(500, 700, by = 10)
)
print(newPositions2)

```

coreInfluence	<i>Find the influence of dates in a pair of Bchronology runs across the core</i>
---------------	--

Description

This function takes as input two [Bchronology](#) runs and compares the uncertainty intervals. It does this by computing the mean uncertainty across the core (type = 'mean') at a specified percentile level (e.g. 95%) and subsequently reporting the reduction/increase in uncertainty between the two runs. Both cores must have the same set of depths/positions at regular intervals.

Usage

```

coreInfluence(
  bchrRun1,
  bchrRun2,
  percentile = 0.95,
  type = c("plot", "summary", "max"),
  ageTolerance = 500,
  ...
)

```

Arguments

bchrRun1	The output of a run of the Bchronology function
bchrRun2	The output of another run of the Bchronology function, possibly with different dates. Note this must have the same value of predictPositions as bchrRun1
percentile	The value of the percentile to compare the uncertainties. Default is 95%
type	if plot will return a plot of the difference in uncertainties at the specified percentile level. If summary will return text output of the reduction in uncertainty at each position. If max will return the position of the maximum decrease in uncertainty and a list of all the positions where the reduction in uncertainty exceeds the value of ageTolerance
ageTolerance	A value in years for which to report the positions at which the reduction in uncertainty exceeds this value.
...	Additional arguments to plot

Details

For example, if the `ageTolerance` value is 500 years, then `coreInfluence` will return all of the positions at which the uncertainty reduction is bigger than 500.

Value

Depending on type will outputs some text and plots providing the influence values for the cores in question.

See Also

[Bchronology](#), [choosePositions](#), [dateInfluence](#) for finding the influence of removing a single date from a core

Examples

```
data(Glendalough)
# Start with a run that remove two dates
GlenOut1 <- Bchronology(
  ages = Glendalough$ages[-c(3:4)],
  ageSds = Glendalough$ageSds[-c(3:4)],
  calCurves = Glendalough$calCurves[-c(3:4)],
  positions = Glendalough$position[-c(3:4)],
  positionThickneses = Glendalough$thickness[-c(3:4)],
  ids = Glendalough$id[-c(3:4)],
  predictPositions = seq(0, 1500, by = 10)
)
GlenOut2 <- Bchronology(
  ages = Glendalough$ages,
  ageSds = Glendalough$ageSds,
  calCurves = Glendalough$calCurves,
  positions = Glendalough$position,
  positionThickneses = Glendalough$thickness,
  ids = Glendalough$id,
  predictPositions = seq(0, 1500, by = 10)
)

# Now compare their influence
coreInfluence(GlenOut1,
  GlenOut2,
  type = c("max", "plot"),
  xlab = "Age (cal years BP)",
  ylab = "Depth (cm)",
  main = "Chronology difference at 95% for
          Glendalough removing two dates",
  las = 1
)
```

createCalCurve	<i>Create a new calibration curve</i>
----------------	---------------------------------------

Description

A function for creating a new calibration curve not already available in Bchron

Usage

```
createCalCurve(
  name,
  calAges,
  uncalAges,
  oneSigma = rep(0, length(calAges)),
  pathToCalCurves = getwd(),
  createFile = TRUE
)
```

Arguments

name	The name of the new calibration curve
calAges	A vector of the calendar/calibrated ages in years before present
uncalAges	A vector of values of uncalibrated ages in appropriate units (e.g. 14C years BP)
oneSigma	The one sigma (one standard deviation) values in uncalibrated units. If left blank it assumes these are all zero
pathToCalCurves	The path to the calibration curves. Will write by default to the working directory
createFile	whether to write out the new file or not. Only turned off for testing purposes

Details

All calibration curves are stored by Bchron in the standard R gzipped text format. You can find the location of the calibration curves by typing `system.file('data', package='Bchron')`. Any created calibration curve will be converted to this format. However R packages are not allowed to write to this directory so it is up to the user to put the resulting calibration curve file in the appropriate directory. It can then be used as in the examples below. However note that re-installing Bchron will likely over-write previously created calibration curves so you should make sure to store the code used to create it. As a short-cut to copying it by hand you can instead use the `file.copy` command in the example below.

Value

No return value, creates a file in your working directory

See Also

[BchronCalibrate](#)

Examples

```
## Not run:
# Load in the calibration curve with:
intcal09 <- read.table(system.file("extdata/intcal09.14c", package = "Bchron"), sep = ",")
# Run createCalCurve
createCalCurve(
  name = "intcal09", calAges = intcal09[, 1],
  uncalAges = intcal09[, 2], oneSigma = intcal09[, 3]
)

# Copy the file to the right place
file.copy(
  from = "intcal09.rda",
  to = system.file("data", package = "Bchron"),
  overwrite = TRUE
) # Only need this if you've run it more than once

# Calibrate the ages under two calibration curves
age_09 <- BchronCalibrate(
  ages = 15500, ageSds = 150,
  calCurves = "intcal09", ids = "My Date",
  pathToCalCurves = getwd()
)
age_20 <- BchronCalibrate(ages = 15500, ageSds = 150, calCurves = "intcal20")

# Finally plot the difference
library(ggplot2)
plot(age_09) +
  geom_line(
    data = as.data.frame(age_20$Date1),
    aes(x = ageGrid, y = densities), col = "red"
  ) +
  ggtitle("Intcal09 vs Intcal20")

## End(Not run)
```

dateInfluence

Find the influence of the dates in a Bchronology run

Description

This function takes as input a [Bchronology](#) run and allows the user to estimate a value of 'influence' for either a particular date (by name or number), for all dates in a core (whichDate = 'all'), or for all internal dates (whichDate = 'internal'). It measures the influence by either the Kullback-Leibler divergence (KL), the absolute mean difference (absMeanDiff), or the absolute median difference (absMedianDiff).

Usage

```
dateInfluence(
  bchrRun,
  whichDate = "all",
  measure = c("KL", "absMeanDiff", "absMedianDiff")
)
```

Arguments

bchrRun	The output of a run of the Bchronology function
whichDate	The chosen date to remove. Either 'all' which removes each date in turn, or 'internal' which removes all but the top/bottom dates, or the date number (in the order same order as in argument 1), or the name of the date from the Bchronology run output file.
measure	Either 'KL' for Kullback Leibler divergence (recommended); or 'absMeanDiff' or 'absMedianDiff' for distances in years from the mean/median age respectively

Details

The KL measure is preferred as it takes account of the full probability distributions but it lacks a simple interpretation. The best way to use it is with whichDate = 'all': the largest value corresponds to the most influential date in the chronology. For simpler interpretation use measure = 'absMeanDiff' or measure = 'absMedianDiff' as for these the influence is measured in years.

When the predictPositions from the original Bchronology run do not include those of the date(s) being left out then the function uses the closest position and reports the change.

Value

Outputs some text providing the influence values for the date(s) in question. If given an assignment value also return a list containing all the probability distributions.

See Also

[Bchronology](#), [summary.BchronologyRun](#), [coreInfluence](#), [choosePositions](#)

Examples

```
data(Glendalough)
GlenOut <- Bchronology(
  ages = Glendalough$ages,
  ageSds = Glendalough$ageSds,
  calCurves = Glendalough$calCurves,
  positions = Glendalough$position,
  positionThicknesses = Glendalough$thickness,
  ids = Glendalough$id,
  predictPositions = seq(0, 1500, by = 10)
)
dateInfluence(GlenOut, whichDate = 4, measure = "absMeanDiff")
```

Glendalough

Glendalough data

Description

Chronology data for Glendalough data set

Usage

```
data(Glendalough)
```

Format

A data frame with 6 observations on the following 6 variables:

`id` ID of each age

`ages` Age in (14C) years BP

`ageSds` Age standard deviations

`position` Depths in cm

`thickness` Thicknesses in cm

`calCurves` Calibration curve for each age

Details

This Glendalough data can be used with [Bchronology](#) or [BchronDensity](#)

Source

Haslett, J., Whiley, M., Bhattacharya, S., Mitchell, F. J. G., Allen, J. R. M., Huntley, B., & Salter-Townshend, M. (2006). Bayesian palaeoclimate reconstruction. *Journal of the Royal Statistical Society, Series A*, 169, 395-438.

hdr

Calculate highest density regions for Bchron calibrated ages

Description

A function for computing highest density regions (HDRs)

Usage

```
hdr(date, prob = 0.95)
```

Arguments

date	A calibrated Bchron date, via e.g. BchronCalibrate
prob	The desired probability interval, in the range(0, 1)

Details

The output of this function is a list of contiguous ranges which cover the probability interval requested. A highest density region might have multiple such ranges if the calibrated date is multi-modal. These differ from credible intervals, which are always contiguous but will not be a good representation of a multi-modal probability distribution.

Value

A list where each element is one of the contiguous sets making up the HDR

See Also

[BchronCalibrate](#)

Examples

```
# Calibrate multiple ages and summarise them
ages <- BchronCalibrate(
  ages = 11553, ageSds = 230,
  calCurves = "intcal20"
)
# Get samples
hdr(ages$Date1)
```

intcal13

Northern hemisphere 2013 calibration curve

Description

Northern hemisphere 2013 calibration curve. The first 3 columns are the calibrated age (in years BP), the radiocarbon age (in 14C years BP), and the 1 sigma standard error (also in 14C years BP).

Usage

```
data(intcal13)
```

Format

A data frame with 5141 observations on 5 variables.

Details

For full details and reference see <http://intcal.org/blurb.html>. For usage details see [BchronCalibrate](#)

intcal20*Northern hemisphere 2020 calibration curve*

Description

Northern hemisphere 2020 calibration curve. The first 3 columns are the calibrated age (in years BP), the radiocarbon age (in 14C years BP), and the 1 sigma standard error (also in 14C years BP).

Usage

```
data(intcal20)
```

Format

A data frame with 9501 observations on 5 variables.

Details

For full details and reference see <http://intcal.org/blurb.html>. For usage details see [BchronCalibrate](#)

marine13*Marine 2013 calibration curve*

Description

Marine 2013 calibration curve. The first 3 columns are the calibrated age (in years BP), the radiocarbon age (in 14C years BP), and the 1 sigma standard error (also in 14C years BP).

Usage

```
data(marine13)
```

Format

A data frame with 4801 observations on 5 variables

Details

For full details and reference see <http://intcal.org/blurb.html>. For usage details see [BchronCalibrate](#)

marine20

Marine 2020 calibration curve

Description

Marine 2020 calibration curve. The first 3 columns are the calibrated age (in years BP), the radio-carbon age (in 14C years BP), and the 1 sigma standard error (also in 14C years BP).

Usage

```
data(marine20)
```

Format

A data frame with 5501 observations on 5 variables

Details

For full details and reference see <http://intcal.org/blurb.html>. For usage details see [BchronCalibrate](#)

normal

Data for dummy calibration of normally distributed ages

Description

Data for dummy calibration of normally distributed ages

Usage

```
data(normal)
```

Format

A data frame with 2 observations on 3 variables.

Details

This is dummy data so that [BchronCalibrate](#) can calibrate normally distributed dates.

plot.BchronCalibratedDates

Plot calibrated dates from a BchronCalibrate run

Description

Plots calibrated radiocarbon dates from a [BchronCalibrate](#) run. Has options to plot on a position (usually depth) scale if supplied with the original run

Usage

```
## S3 method for class 'BchronCalibratedDates'
plot(
  x,
  date = NULL,
  withPositions = ifelse(length(x) > 1 & !is.null(x[[1]]$positions) & !includeCal, TRUE,
    FALSE),
  includeCal = FALSE,
  dateHeight = 100,
  dateLabels = TRUE,
  dateLabelSize = 2,
  nudgeX = 0,
  nudgeY = 0,
  fillCol = rgb(47/255, 79/255, 79/255, 0.5),
  withHDR = TRUE,
  ageScale = c("bp", "bc", "b2k"),
  scaleReverse = TRUE,
  pathToCalCurves = system.file("data", package = "Bchron"),
  ...
)
```

Arguments

x	Output from BchronCalibrate
date	Either numbers or date names to plot (only used if multiple dates have been calibrated)
withPositions	Whether to plot with positions (i.e. using the position values as the y axis). By default TRUE if x has more than one date and contains positions
includeCal	Whether to plot the date alongside the calibration curve (with 95% uncertainty bands) and the normally distributed uncalibrated date.
dateHeight	The height of the dates in the plot in the same units as the position values. Only relevant if withPositions=TRUE.
dateLabels	Whether to add the names of the dates to the left of them. Default TRUE
dateLabelSize	Size of the date labels

nudgeX	The amount to move the date labels in the x direction. Can be negative. See geom_text for details
nudgeY	The amount to move the date labels in the y direction. Can be negative. See geom_text for details
fillCol	A colour to fill the date densities when withPositions is TRUE, or HDR ranges when it is FALSE
withHDR	Whether to plot the 95% highest density region values
ageScale	Either bp for years before present, bc for years BC/AD (BC will be negative), b2k for years before 2000. Others not supported (yet).
scaleReverse	Whether to reverse the x-axis scale. Defaults to TRUE which works best for dates presented in e.g. years BP
pathToCalCurves	The Bchron path to calibration curves. Defaults to the package location might need to be set to another folder if user defined calibration curves are being used
...	Other arguments to plot (currently ignored)

Details

These plots are intended to be pretty basic and used simply for quick information. Users are encouraged to learn the R plotting features to produce publication quality graphics

Value

A ggplot object containing the plot of the calibrated dates

See Also

[BchronCalibrate](#), [Bchronology](#), [BchronRSL](#), [BchronDensity](#), [BchronDensityFast](#)

`plot.BchronDensityRun` *Plot output from BchronDensity*

Description

Plot output from BchronDensity

Usage

```
## S3 method for class 'BchronDensityRun'
plot(
  x,
  plotDates = TRUE,
  plotRawSum = FALSE,
  plotPhase = TRUE,
  phaseProb = 0.95,
  dateTransparency = 0.4,
  ...
)
```

Arguments

x	Output from BchronDensity
plotDates	Whether to plot the individual calibrated dates
plotRawSum	Whether to plot the raw sum of the probability distributions
plotPhase	Whether to plot the phase values
phaseProb	The probability value for the phase identification
dateTransparency	The transparency value for the dates (default 0.4)
...	Other graphical commands. See par

Value

A plot object of the density run

See Also

See [BchronDensity](#) for examples, also [Bchronology](#), [BchronRSL](#), and [BchronDensityFast](#) for a faster approximate version of this function

```
plot.BchronDensityRunFast
```

Plot run from BchronDensityFast

Description

Plots output from [BchronDensityFast](#)

Usage

```
## S3 method for class 'BchronDensityRunFast'
plot(x, plotDates = TRUE, plotSum = FALSE, dateTransparency = 0.4, ...)
```

Arguments

x	Output from BchronDensityFast
plotDates	Whether to include individual age pdfs (default TRUE)
plotSum	Whether to include sum of age pdfs (default FALSE)
dateTransparency	The transparency value for the dates (default 0.4)
...	Other graphical parameters, see par

Details

Creates a basic plot of output for a run of [BchronDensityFast](#)

Value

A plot object of the density run

See Also

Examples in [BchronDensityFast](#), and see [BchronDensity](#), for a slower, more accurate version of this function

plot.BchronologyRun *Plot output from Bchronology*

Description

Plots output from a run of [Bchronology](#)

Usage

```
## S3 method for class 'BchronologyRun'
plot(
  x,
  dateHeight = 100,
  dateLabels = TRUE,
  dateLabelSize = 2,
  dateCol = rgb(47/255, 79/255, 79/255, 0.5),
  chronCol = "deepskyblue4",
  chronTransparency = 0.75,
  alpha = 0.95,
  nudgeX = 0,
  nudgeY = 0,
  expandX = if (dateLabels) {
    c(0.1, 0)
  } else {
    c(0, 0)
  },
  expandY = c(0.05, 0),
  ageScale = c("bp", "bc", "b2k"),
  scaleReverse = TRUE,
  ...
)
```

Arguments

x	The object created by Bchronology
dateHeight	The height of the dates in the plot (on the same scale as the positions)
dateLabels	Whether to label the dates on the vertical axis (default TRUE)
dateLabelSize	The size of the date labels

dateCol	The colour of the date labels
chronCol	The colour of the chronology uncertainty ribbon to be plotted
chronTransparency	The amount of transparency for the chronology ribbon
alpha	The credible interval of the chronology run to be plotted. Defaults to 95 percent
nudgeX	The amount to move the date labels in the x direction. Can be negative. See geom_text for details
nudgeY	The amount to move the date labels in the y direction. Can be negative. See geom_text for details
expandX	The amount to expand the horizontal axis in case part are missed off the plot. See expand_limits for details
expandY	The amount to expand the vertical axis in case part are missed off the plot. See expand_limits for details
ageScale	Either bp for years before present, bc for years BC/AD (BC will be negative), b2k for years before 2000. Others not supported (yet).
scaleReverse	Whether to reverse the x-axis scale. Defaults to TRUE which works best for dates presented in e.g. years BP
...	Other arguments to plot (currently ignored)

Details

Creates a simple plot of the chronology output. The height of the date densities in the plots can be manipulated via the dateHeight argument which is represented in the same units as the positions/depths provided. More detailed plots can be created by manipulating the Bchronology object as required.

Value

A ggplot2 object of the chronology run

See Also

For examples see [Bchronology](#). Also [BchronCalibrate](#), [BchronRSL](#), [BchronDensity](#), [BchronDensityFast](#)

plot.BchronRSLRun	<i>Plot output from BchronRSL</i>
-------------------	-----------------------------------

Description

Plot output from the [BchronRSL](#) function

Usage

```
## S3 method for class 'BchronRSLRun'
plot(
  x,
  type = c("RSL", "rate", "accel"),
  alpha = 0.95,
  ellipseCol = "darkslategray",
  lineCol = "deepskyblue4",
  ...
)
```

Arguments

x	An object created by BchronRSL
type	One of RSL, rate, or accel. If RSL produces a plot of RSL estimates from the model. If rate, produces rate estimates. If accel produces acceleration estimates.
alpha	confidence level used for plotting ellipses
ellipseCol	The colour of the ellipse used for plotting dates
lineCol	The colour of the sea level curve lines
...	Other arguments to plot (currently ignored)

Value

A ggplot2 object of the RSL run

See Also

[BchronCalibrate](#), [Bchronology](#), [BchronRSL](#), [BchronDensity](#), [BchronDensityFast](#)

predict.BchronologyRun

Predict ages of other positions for a BchronologyRun object

Description

This function will predict the ages of new positions (usually depths) based on a previous run of the function [Bchronology](#). It will also allow for thickness uncertainties to be included in the resulting ages, for example when the age of a particular event is desired

Usage

```
## S3 method for class 'BchronologyRun'
predict(
  object,
  newPositions,
  newPositionThicknesses = NULL,
  maxExtrap = 500,
  ...
)
```

Arguments

object	Output from a run of Bchronology
newPositions	A vector of new positions at which to find ages
newPositionThicknesses	A vector of thicknesses for the above positions. Must be the same length as newPositions. If NULL then assumed zero
maxExtrap	The maximum new of extrapolation attempts. It might be worth increasing this if you are extrapolating a long way from the other dated positions
...	Other arguments to predict (not currently supported)

Value

A matrix of dimension num_samples by num_positions so that each row represents a set of monotonic sample predicted ages

See Also

[BchronCalibrate](#), [Bchronology](#) [BchronRSL](#), [BchronDensity](#), [BchronDensityFast](#)

sampleAges

Get sample ages from a set of Bchron calibrated dates

Description

A function for extracting sample ages from Bchron calibrated dates

Usage

```
sampleAges(CalDates, n_samp = 10000)
```

Arguments

CalDates	A list created from either BchronCalibrate .
n_samp	The desired number of samples

Details

Sometimes it is useful to have a set of sample calendar ages for your calibrated dates. For example the samples might be required to create a credible/confidence interval, or to create another non-trivial function of calibrated dates, such as differences. By default the [BchronCalibrate](#) function provides a grid of ages and an associated density, similar to OxCal. This function extracts that information and uses the [sample](#) function to output the desired number of samples

Value

A vector of length `n_samp` containing sample ages for the specified date

See Also

[BchronCalibrate](#)

Examples

```
# Calibrate multiple ages and summarise them
ages <- BchronCalibrate(
  ages = c(3445, 11553, 7456), ageSds = c(50, 230, 110),
  calCurves = c("intcal20", "intcal20", "shcal20")
)
# Get samples
age_samples <- sampleAges(ages)
# Create a credible interval and the median for each date
apply(age_samples, 2, quantile, probs = c(0.05, 0.5, 0.95))
```

shcal13

Southern hemisphere 2013 calibration curve

Description

Southern hemisphere 2013 calibration curve. The first 3 columns are the calibrated age (in years BP), the radiocarbon age (in 14C years BP), and the 1 sigma standard error (also in 14C years BP).

Usage

```
data(shcal13)
```

Format

A data frame with 5141 observations on 5 variables.

Details

For full details and reference see <http://intcal.org/blurb.html>. For usage details see [BchronCalibrate](#)

shcal20	<i>Southern hemisphere 2020 calibration curve</i>
---------	---

Description

Southern hemisphere 2020 calibration curve. The first 3 columns are the calibrated age (in years BP), the radiocarbon age (in 14C years BP), and the 1 sigma standard error (also in 14C years BP).

Usage

```
data(shcal20)
```

Format

A data frame with 9501 observations on 5 variables.

Details

For full details and reference see <http://intcal.org/blurb.html>. For usage details see [BchronCalibrate](#)

Sluggan	<i>Sluggan Moss data</i>
---------	--------------------------

Description

Chronology data for Sluggan Moss data set

Usage

```
data(Sluggan)
```

Format

A data frame with 31 observations on the following 6 variables:

id ID of each age
 ages Age in (14C) years BP
 ageSds Age standard deviations
 position Depths in cm
 thickness Thicknesses in cm
 calCurves Calibration curve for each age

Details

This Sluggan Moss data can be downloaded from the European Pollen Database: <https://epdweblog.org/>. For usage see [Bchronology](#) or [BchronDensity](#)

Source

Smith, A. G., & Goddard, I. C. (1991). A 12,500 year record of vegetational history at Sluggan Bog, Co. Antrim, N. Ireland (incorporating a pollen zone scheme for the non-specialist). *New Phytologist*, 118, 167-187.

```
summary.BchronCalibratedDates
```

Summarise a BchronCalibrate object

Description

Produces summary output from a [BchronCalibrate](#) run, including the highest density regions for the calibrated ages for given probability levels

Usage

```
## S3 method for class 'BchronCalibratedDates'
summary(object, prob = 95, ..., digits = max(3, getOption("digits") - 3))
```

Arguments

object	The output of a run of BchronCalibrate
prob	A percentage value (between 0 and 100) at which the highest density regions for each age are calculated
...	Further arguments (not currently supported)
digits	Significant digits to display (not currently supported)

Value

A list of highest density regions for each calibrated date in the object

See Also

[BchronCalibrate](#), [Bchronology](#), [BchronRSL](#), [BchronDensity](#), [BchronDensityFast](#)

summary.BchronDensityRun

Summarise a Bchron density object

Description

Summarise a [BchronDensity](#) object

Usage

```
## S3 method for class 'BchronDensityRun'
summary(object, prob = 0.95, ..., digits = max(3, getOption("digits") - 3))
```

Arguments

object	Output from a run of BchronDensity
prob	Probability for identifying phases
...	Other arguments (not currently supported)
digits	Number of digits to report values

Value

A list of highest density regions for each phase in the object

See Also

[BchronDensity](#)

summary.BchronologyRun

Summarise a Bchronology object

Description

Summarise a [Bchronology](#) object

Usage

```
## S3 method for class 'BchronologyRun'
summary(
  object,
  type = c("quantiles", "outliers", "convergence", "sed_rate", "acc_rate", "max_var"),
  probs = c(0.025, 0.25, 0.5, 0.75, 0.975),
  acc_probs = c(0.05, 0.95),
  useExisting = TRUE,
```

```

    numPos = 3,
    ...,
    digits = max(3, getOption("digits") - 3)
  )

```

Arguments

object	Output from a run of Bchronology
type	Type of output required. The default (quantiles) gives the quantiles of the ages for each position in predictPositions from Bchronology . The other options provide outlier probabilities, convergence diagnostics, accumulation rates, sedimentation rate, and positions of maximum age variance
probs	Probabilities (between 0 and 1) at which to summarise the predicted chronologies
acc_probs	The age range over which to calculate accumulation rates (the default is between the 5% and 95% quantiles of all predicted ages)
useExisting	Whether to use the predicted chronologies/positions to calculate the sedimentation rate (if TRUE - default) or to re-create them based on a unit-scaled position grid (if FALSE). The latter will be a little bit slower but will provide better sedimentation rate estimates if the original positions are not on a unit scale (e.g. each cm)
numPos	The number of positions at which to provide the maximum variance
...	Other arguments (not currently supported)
digits	Number of digits to report values

Value

A data frame summarising the Bchronology object depending on the type of summary requested. For quantiles, a data frame with the quantiles for each position. For outliers, a data frame with outlier probabilities. For convergence, a data frame with p-values for convergence diagnostics. For sedimentation and accumulation rates, a data frame with the rates at each position/age. For maximum variance, a vector of positions with maximum age variance.

See Also

[BchronCalibrate](#), [Bchronology](#) [BchronRSL](#), [BchronDensity](#), [BchronDensityFast](#)

summary.BchronRSLRun *Summarise a BchronRSL run*

Description

Summarise a [BchronRSL](#) run

Usage

```
## S3 method for class 'BchronRSLRun'
summary(
  object,
  type = c("parameters", "RSL", "rate", "accel"),
  age_grid = NULL,
  ...
)
```

Arguments

object	The output from a run of BchronRSL
type	One of parameters, RSL, rate, or accel. If parameters, provides posterior credibility intervals of the regression coefficients. If RSL provides predicted RSL values. If rate, provides rate estimates. If accel provides acceleration estimates.
age_grid	An optional age grid for computing RSL, rate, or acceleration estimates. If not provided uses the age range of the Bchronology run
...	Other arguments to functions (not currently implemented)

Value

A summary of the BchronRSL run, including posterior medians and credible intervals for the regression coefficients, RSL estimates, rate estimates, and acceleration estimates.

See Also

[BchronCalibrate](#), [Bchronology](#), [BchronRSL](#), [BchronDensity](#), [BchronDensityFast](#)

TestChronData	<i>Example chronology file for use with the BchronRSL function.</i>
---------------	---

Description

Some example chronology data for use with the [BchronRSL](#) function

Usage

```
data(TestChronData)
```

Format

A data frame with 27 observations on the following 6 variables:

id ID names
 ages Ages in years BP
 ageSds Ages standard deviations in years BP
 position Depths in cm
 thickness Thicknesses in cm
 calCurves Calibration curve for each age

Source

Andrew C. Parnell and W. Roland Gehrels (2013) 'Using chronological models in late holocene sea level reconstructions from salt marsh sediments' In: I. Shennan, B.P. Horton, and A.J. Long (eds). Handbook of Sea Level Research. Chichester: Wiley

 TestRSLData

Relative sea level data

Description

A set of relative sea level data for use with [BchronRSL](#)

Usage

```
data(TestRSLData)
```

Format

A data frame with 24 observations on the following 3 variables:

Depth Depth in cm
 RSL Relative sea level in m
 Sigma Standard deviation of RSL measurement

Source

Andrew C. Parnell and W. Roland Gehrels (2013) 'Using chronological models in late holocene sea level reconstructions from salt marsh sediments' In: I. Shennan, B.P. Horton, and A.J. Long (eds). Handbook of Sea Level Research. Chichester: Wiley

unCalibrate	<i>Uncalibrate a Radiocarbon date</i>
-------------	---------------------------------------

Description

Uncalibrate a Radiocarbon date

Usage

```
unCalibrate(
  calAges,
  calCurve = "intcal20",
  type = c("samples", "ages"),
  pathToCalCurves = system.file("data", package = "Bchron"),
  ...
)
```

Arguments

calAges	Either a vector of calibrated ages (when type = 'ages'), or a vector of calibrated samples (type = 'samples')
calCurve	he calibration curve to use. Only a single calibration curve is currently supported
type	Either 'ages' which uncalibrates a calibrated age values without error (i.e. just a lookup on the calibration curve), or a 'samples' which estimates both an uncalibrated mean age and a standard deviation
pathToCalCurves	The path to the calibration curve directory. Defaults to the location of the standard calibration curves given in the package
...	Other arguments to the optim function used to match the probability distributions under type = 'samples'

Value

Either a vector of uncalibrated ages (type = 'ages') or a list containing the estimated mean age and standard deviation (type = 'samples')

Examples

```
# Single version outputting just an uncalibrated age
unCalibrate(2350, type = "ages")

# Vector version giving a vector of uncalibrated ages
unCalibrate(
  calAge = c(2350, 4750, 11440),
  calCurve = "shcal20",
  type = "ages"
)
```

```
# A version where calibrated standard deviations are required too
calAge <- BchronCalibrate(
  ages = 11255,
  ageSds = 25,
  calCurves = "intcal20"
)
calSampleAges <- sampleAges(calAge)

# Uncalibrate the above
unCalibrate(calSampleAges,
  type = "samples"
)
```

Index

* datasets

- Glendalough, [25](#)
- intcal13, [26](#)
- intcal20, [27](#)
- marine13, [27](#)
- marine20, [28](#)
- normal, [28](#)
- shcal13, [36](#)
- shcal20, [37](#)
- Sluggan, [37](#)
- TestChronData, [41](#)
- TestRSLData, [42](#)

Bchron, [3](#)

Bchron-package (Bchron), [3](#)

BchronCalibrate, [3](#), [4](#), [6](#), [10](#), [12](#), [15](#), [17](#), [22](#),
[26–30](#), [33–38](#), [40](#), [41](#)

BchronCheck, [6](#)

BchronDensity, [3](#), [5](#), [9](#), [11](#), [12](#), [15](#), [17](#), [25](#),
[30–35](#), [37–41](#)

BchronDensityFast, [3](#), [5](#), [10](#), [11](#), [15](#), [17](#),
[30–35](#), [38](#), [40](#), [41](#)

Bchronology, [3](#), [5](#), [6](#), [10](#), [12](#), [12](#), [17–21](#),
[23–25](#), [30–35](#), [37–41](#)

BchronRSL, [3](#), [5](#), [10](#), [12](#), [15](#), [16](#), [30](#), [31](#), [33–35](#),
[38](#), [40–42](#)

choosePositions, [18](#), [21](#), [24](#)

coreInfluence, [20](#), [24](#)

createCalCurve, [5](#), [22](#)

dateInfluence, [21](#), [23](#)

densityMclust, [11](#), [12](#)

expand_limits, [33](#)

geom_text, [30](#), [33](#)

Glendalough, [25](#)

hdr, [25](#)

intcal13, [26](#)

intcal20, [27](#)

marine13, [27](#)

marine20, [28](#)

normal, [28](#)

optim, [43](#)

par, [31](#)

plot.BchronCalibratedDates, [29](#)

plot.BchronDensityRun, [30](#)

plot.BchronDensityRunFast, [31](#)

plot.BchronologyRun, [32](#)

plot.BchronRSLRun, [33](#)

predict.BchronologyRun, [34](#)

sample, [36](#)

sampleAges, [35](#)

shcal13, [36](#)

shcal20, [37](#)

Sluggan, [37](#)

summary.BchronCalibratedDates, [38](#)

summary.BchronDensityRun, [39](#)

summary.BchronologyRun, [24](#), [39](#)

summary.BchronRSLRun, [40](#)

TestChronData, [41](#)

TestRSLData, [42](#)

unCalibrate, [18](#), [19](#), [43](#)