

# Package ‘MolgenisArmadillo’

December 6, 2025

**Type** Package

**Version** 2.9.3

**Title** Armadillo Client for the Armadillo Service

**Description** A set of functions to manage data shared on a  
'MOLGENIS Armadillo' server.

**Maintainer** Mariska Slofstra <m.k.slofstra@umcg.nl>

**Depends** R (>= 4.1.0)

**Imports** base64enc, httr, urltools, dplyr, purrr, stringr, tidyr,  
tibble, MolgenisAuth (>= 0.0.25), arrow, rlist, httr2, readr,  
cli

**Suggests** stringi, withr, knitr, testthat, webmockr, mockery, datasets,  
rmarkdown

**License** LGPL (>= 2.1)

**URL** <https://github.com/molgenis/molgenis-r-armadillo/>,  
<https://molgenis.github.io/molgenis-r-armadillo/>

**BugReports** <https://github.com/molgenis/molgenis-r-armadillo/issues/>

**RoxygenNote** 7.3.3

**VignetteBuilder** knitr

**Encoding** UTF-8

**Config/testthat/edition** 3

**NeedsCompilation** no

**Author** Mariska Slofstra [aut, cre] (ORCID:  
<<https://orcid.org/0000-0002-0400-0468>>),  
Sido Haakma [aut] (ORCID: <<https://orcid.org/0000-0003-1278-9144>>),  
Tommy de Boer [aut] (ORCID: <<https://orcid.org/0000-0002-4492-7225>>),  
Fleur Kelpin [aut] (ORCID: <<https://orcid.org/0000-0003-1527-5130>>),  
Morris Swertz [aut] (ORCID: <<https://orcid.org/0000-0002-0979-3401>>),  
Tim Cadman [aut] (ORCID: <<https://orcid.org/0000-0002-7682-5645>>)

**Repository** CRAN

**Date/Publication** 2025-12-06 13:10:14 UTC

## Contents

|                                                 |                    |
|-------------------------------------------------|--------------------|
| <a href="#">.add_slash_if_missing</a>           | <a href="#">2</a>  |
| <a href="#">.compress_resource</a>              | <a href="#">3</a>  |
| <a href="#">.compress_table</a>                 | <a href="#">3</a>  |
| <a href="#">.format_api_posts</a>               | <a href="#">4</a>  |
| <a href="#">.get_linkfile_content</a>           | <a href="#">4</a>  |
| <a href="#">.load_linked_table</a>              | <a href="#">5</a>  |
| <a href="#">.load_resource</a>                  | <a href="#">5</a>  |
| <a href="#">.load_table</a>                     | <a href="#">6</a>  |
| <a href="#">armadillo.copy_resource</a>         | <a href="#">6</a>  |
| <a href="#">armadillo.copy_table</a>            | <a href="#">7</a>  |
| <a href="#">armadillo.create_project</a>        | <a href="#">8</a>  |
| <a href="#">armadillo.delete_project</a>        | <a href="#">9</a>  |
| <a href="#">armadillo.delete_project_folder</a> | <a href="#">9</a>  |
| <a href="#">armadillo.delete_resource</a>       | <a href="#">10</a> |
| <a href="#">armadillo.delete_table</a>          | <a href="#">10</a> |
| <a href="#">armadillo.get_projects_info</a>     | <a href="#">11</a> |
| <a href="#">armadillo.get_project_users</a>     | <a href="#">11</a> |
| <a href="#">armadillo.install_packages</a>      | <a href="#">12</a> |
| <a href="#">armadillo.list_projects</a>         | <a href="#">12</a> |
| <a href="#">armadillo.list_resources</a>        | <a href="#">13</a> |
| <a href="#">armadillo.list_tables</a>           | <a href="#">14</a> |
| <a href="#">armadillo.load_resource</a>         | <a href="#">14</a> |
| <a href="#">armadillo.load_table</a>            | <a href="#">15</a> |
| <a href="#">armadillo.login</a>                 | <a href="#">16</a> |
| <a href="#">armadillo.login_basic</a>           | <a href="#">16</a> |
| <a href="#">armadillo.move_resource</a>         | <a href="#">17</a> |
| <a href="#">armadillo.move_table</a>            | <a href="#">18</a> |
| <a href="#">armadillo.subset</a>                | <a href="#">19</a> |
| <a href="#">armadillo.subset_definition</a>     | <a href="#">20</a> |
| <a href="#">armadillo.upload_resource</a>       | <a href="#">21</a> |
| <a href="#">armadillo.upload_table</a>          | <a href="#">22</a> |
| <b>Index</b>                                    | <a href="#">23</a> |

---

[.add\\_slash\\_if\\_missing](#) *Add a Slash to a URL if Missing*

---

### Description

This function ensures that a given URL string ends with a slash ('/'). If the URL does not end with a slash, it appends one.

### Usage

```
.add_slash_if_missing(url)
```

### Arguments

url                      A character string representing the URL.

### Value

A character string with a trailing slash if it was missing.

---

.compress\_resource      *Helper function for compressing to an RDS file*

---

### Description

Helper function for compressing to an RDS file

### Usage

```
.compress_resource(resource, file)
```

### Arguments

resource                the resource to write to file  
file                     the name of the file (without extension)

### Value

the extension of the file

---

.compress\_table          *Helper function for compressing to a parquet file*

---

### Description

Helper function for compressing to a parquet file

### Usage

```
.compress_table(table, file)
```

### Arguments

table                    the table to write to file  
file                     the name of the file (without extension)

### Value

the extension of the file

---

|                                |                                                     |
|--------------------------------|-----------------------------------------------------|
| <code>.format_api_posts</code> | <i>Formats API posts based on subset definition</i> |
|--------------------------------|-----------------------------------------------------|

---

**Description**

Formats API posts based on subset definition

**Usage**

```
.format_api_posts(posts, subset_def)
```

**Arguments**

|                         |                                       |
|-------------------------|---------------------------------------|
| <code>posts</code>      | A list of API posts                   |
| <code>subset_def</code> | A tibble containing subset definition |

**Value**

A tibble consisting of original `subset_def` with columns 'posts' and 'status' appended.

---

|                                    |                                                          |
|------------------------------------|----------------------------------------------------------|
| <code>.get_linkfile_content</code> | <i>Helper function to get the contents of a linkfile</i> |
|------------------------------------|----------------------------------------------------------|

---

**Description**

Helper function to get the contents of a linkfile

**Usage**

```
.get_linkfile_content(project, object_name)
```

**Arguments**

|                          |                                          |
|--------------------------|------------------------------------------|
| <code>project</code>     | projectname where the linkfile is stored |
| <code>object_name</code> | folder/name of linkfile                  |

**Value**

the contents of the linkfile

---

|                                 |                                                                         |
|---------------------------------|-------------------------------------------------------------------------|
| <code>.load_linked_table</code> | <i>Helper function to extract the source parquet file in a linkfile</i> |
|---------------------------------|-------------------------------------------------------------------------|

---

### **Description**

Helper function to extract the source parquet file in a linkfile

### **Usage**

```
.load_linked_table(file, columns)
```

### **Arguments**

|                      |                                                      |
|----------------------|------------------------------------------------------|
| <code>file</code>    | source table parquet file                            |
| <code>columns</code> | character list of columns to select from source file |

### **Value**

the contents of the file, as data frame

---

|                             |                                               |
|-----------------------------|-----------------------------------------------|
| <code>.load_resource</code> | <i>Helper function to extract an RDS file</i> |
|-----------------------------|-----------------------------------------------|

---

### **Description**

Helper function to extract an RDS file

### **Usage**

```
.load_resource(file)
```

### **Arguments**

|                   |                 |
|-------------------|-----------------|
| <code>file</code> | file to extract |
|-------------------|-----------------|

### **Value**

the contents of the file

---

|                          |                                                  |
|--------------------------|--------------------------------------------------|
| <code>.load_table</code> | <i>Helper function to extract a parquet file</i> |
|--------------------------|--------------------------------------------------|

---

**Description**

Helper function to extract a parquet file

**Usage**

```
.load_table(file)
```

**Arguments**

|                   |                 |
|-------------------|-----------------|
| <code>file</code> | file to extract |
|-------------------|-----------------|

**Value**

the contents of the file, as data frame

---

|                                      |                      |
|--------------------------------------|----------------------|
| <code>armadillo.copy_resource</code> | <i>Copy resource</i> |
|--------------------------------------|----------------------|

---

**Description**

Copy resource

**Usage**

```
armadillo.copy_resource(  
  project,  
  folder,  
  name,  
  new_folder = folder,  
  new_name = name  
)
```

**Arguments**

|                         |                                                                   |
|-------------------------|-------------------------------------------------------------------|
| <code>project</code>    | study or other variable collection                                |
| <code>folder</code>     | the folder containing the resource                                |
| <code>name</code>       | specific resource for copy action                                 |
| <code>new_folder</code> | name of the folder in which to place the copy, defaults to folder |
| <code>new_name</code>   | name of the copy, defaults to name                                |

**Value**

the response from the server

**Examples**

```
## Not run:
armadillo.copy_resource(
  project = "gecko",
  folder = "core_all",
  name = "table1",
  new_folder = "core_all_v2",
)

## End(Not run)
```

---

armadillo.copy\_table    *Copy table*

---

**Description**

Copy table

**Usage**

```
armadillo.copy_table(
  project,
  folder,
  name,
  new_folder = folder,
  new_name = name
)
```

**Arguments**

|            |                                                                   |
|------------|-------------------------------------------------------------------|
| project    | study or other variable collection                                |
| folder     | the folder containing the table                                   |
| name       | specific table for copy action                                    |
| new_folder | name of the folder in which to place the copy, defaults to folder |
| new_name   | name of the copy, defaults to name                                |

**Value**

the response from the server

**Examples**

```
## Not run:
armadillo.copy_table(
  project = "gecko",
  folder = "core_all",
  name = "table1",
  new_folder = "core_all_v2",
)

## End(Not run)
```

---

```
armadillo.create_project
```

*Create a project for a variable collection*

---

**Description**

Create a project for a variable collection

**Usage**

```
armadillo.create_project(
  project_name = NULL,
  users = NULL,
  overwrite_existing = "choose"
)
```

**Arguments**

|                    |                                                                                                                                                                                                                                                                   |
|--------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| project_name       | The name of the project to create. The project name <ul style="list-style-type: none"> <li>• cannot be empty.</li> <li>• must be no more than 56 characters.</li> <li>• cannot end with a -.</li> <li>• must consist of lowercase letters and numbers.</li> </ul> |
| users              | A list collection of the users that should have access to the project                                                                                                                                                                                             |
| overwrite_existing | Character, specifying action to take if project still exists: 'choose' (default) displays a menu giving the option to overwrite or not, 'yes' overwrites the existing project and 'no' exists the function with a message.                                        |

**Examples**

```
## Not run:
armadillo.create_project("gecko")

## End(Not run)
```



---

```
armadillo.delete_project
```

*Delete project*

---

**Description**

A project represents usually a study or collection of variables

**Usage**

```
armadillo.delete_project(project_name)
```

**Arguments**

project\_name     the name of the study or collection of variables name

**Examples**

```
## Not run:  
armadillo.delete_project(project_name = "gecko")  
  
## End(Not run)
```

---

```
armadillo.delete_project_folder
```

*Delete project folder*

---

**Description**

Delete project folder

**Usage**

```
armadillo.delete_project_folder(project, folder)
```

**Arguments**

project            project to delete the object from  
folder            folder to delete the object from

armadillo.delete\_resource  
*Delete resource*

---

**Description**

Delete resource

**Usage**

```
armadillo.delete_resource(project, folder, name)
```

**Arguments**

|         |                                     |
|---------|-------------------------------------|
| project | project to delete the resource from |
| folder  | folder to delete the resource from  |
| name    | resource name                       |

**Examples**

```
## Not run:  
armadillo.delete_resource(  
  project = "gecko",  
  folder = "core_all",  
  name = "table1"  
)  
  
## End(Not run)
```

---

armadillo.delete\_table  
*Delete table*

---

**Description**

Delete table

**Usage**

```
armadillo.delete_table(project, folder, name)
```

**Arguments**

|         |                                  |
|---------|----------------------------------|
| project | project to delete the table from |
| folder  | folder to delete the table from  |
| name    | table name                       |

**Examples**

```
## Not run:
armadillo.delete_table(
  project = "gecko",
  folder = "core_all",
  name = "table1"
)

## End(Not run)
```

---

armadillo.get\_projects\_info  
*Gets the Projects information*

---

**Description**

Gets the Projects information

**Usage**

```
armadillo.get_projects_info()
```

**Value**

the projects and their information

**Examples**

```
## Not run:
armadillo.get_projects_info()

## End(Not run)
```

---

armadillo.get\_project\_users  
*Gets the users of an given project name*

---

**Description**

Gets the users of an given project name

**Usage**

```
armadillo.get_project_users(project_name)
```

**Arguments**

project\_name      the name of the project to extract the users from

**Value**

List of all users within "project\_name"

**Examples**

```
## Not run:
armadillo.get_project_users("some-project")

## End(Not run)
```

---

```
armadillo.install_packages
      Install package
```

---

**Description**

Installs a user defined package into the provided profile. The package is automatically whitelisted after installation. Only available during development.

**Usage**

```
armadillo.install_packages(paths, profile = "default")
```

**Arguments**

paths              the path(s) to the package(s), can be a vector or a string  
profile            the selected profile

---

```
armadillo.list_projects
      List the projects
```

---

**Description**

List the projects

**Usage**

```
armadillo.list_projects()
```

**Value**

the projects

**Examples**

```
## Not run:  
armadillo.list_projects()  
  
## End(Not run)
```

---

```
armadillo.list_resources
```

*List the resources in a project*

---

**Description**

List the resources in a project

**Usage**

```
armadillo.list_resources(project)
```

**Arguments**

project            the shared project in which the resources are located

**Value**

the resources in the project

**Examples**

```
## Not run:  
armadillo.list_resources("gecko")  
  
## End(Not run)
```

---

`armadillo.list_tables` *List the tables in a project*

---

**Description**

List the tables in a project

**Usage**

```
armadillo.list_tables(project)
```

**Arguments**

`project`                      the shared project in which the tables are located

**Value**

the table names, without the extension

**Examples**

```
## Not run:  
armadillo.list_tables("gecko")  
  
## End(Not run)
```

---

`armadillo.load_resource`  
*Load a resource from a project*

---

**Description**

Load a resource from a project

**Usage**

```
armadillo.load_resource(project, folder, name)
```

**Arguments**

`project`                      study or collection variables  
`folder`                        the folder containing the resource  
`name`                          name of the resource

**Value**

the loaded resource

**Examples**

```
## Not run:
armadillo.load_resource(
  project = "gecko",
  folder = "core_all",
  name = "lc_core_1"
)

## End(Not run)
```

---

armadillo.load\_table    *Load a table from a project*

---

**Description**

Load a table from a project

**Usage**

```
armadillo.load_table(project, folder, name)
```

**Arguments**

|         |                                 |
|---------|---------------------------------|
| project | study or collection variables   |
| folder  | the folder containing the table |
| name    | name of the table               |

**Value**

the contents of the table file, as data frame

**Examples**

```
## Not run:
armadillo.load_table(
  project = "gecko",
  folder = "core_all",
  name = "lc_core_1"
)

## End(Not run)
```

|                 |              |
|-----------------|--------------|
| armadillo.login | <i>Login</i> |
|-----------------|--------------|

---

**Description**

Interactively obtains an id token and uses it to create a session token for an Armadillo Service

**Usage**

```
armadillo.login(armadillo)
```

**Arguments**

|           |                              |
|-----------|------------------------------|
| armadillo | URL of the Armadillo server, |
|-----------|------------------------------|

**Value**

the id token

**Examples**

```
## Not run:  
armadillo.login(  
  "https://armadillo.dev.molgenis.org"  
)  
armadillo.login("http://localhost:8080")  
  
## End(Not run)
```

---

|                       |                                                                             |
|-----------------------|-----------------------------------------------------------------------------|
| armadillo.login_basic | <i>Login with username / password (meant for dev and test environments)</i> |
|-----------------------|-----------------------------------------------------------------------------|

---

**Description**

Login with username / password (meant for dev and test environments)

**Usage**

```
armadillo.login_basic(armadillo, username, password)
```

**Arguments**

|           |                             |
|-----------|-----------------------------|
| armadillo | URL of the Armadillo server |
| username  | the username                |
| password  | the password                |



## Examples

```
## Not run:
armadillo.login(
  "https://armadillo.dev.molgenis.org", "admin", "admin"
)
armadillo.login("http://localhost:8080", "admin", "admin")

## End(Not run)
```

---

armadillo.move\_resource

*Move the resource*

---

## Description

Move the resource

## Usage

```
armadillo.move_resource(
  project,
  folder,
  name,
  new_folder = folder,
  new_name = name
)
```

## Arguments

|            |                                                        |
|------------|--------------------------------------------------------|
| project    | a study or collection of variables                     |
| folder     | the folder containing the resource to move             |
| name       | a resource to move                                     |
| new_folder | the folder to move the resource to, defaults to folder |
| new_name   | use to rename the file, defaults to name               |

## Value

NULL, invisibly

## Examples

```
## Not run:
armadillo.move_resource(
  project = "gecko",
  folder = "core_all",
  name = "table1",
```

```
    new_folder = "core_all_v2",  
  )  
  
## End(Not run)
```

---

armadillo.move\_table    *Move the table*

---

## Description

Move the table

## Usage

```
armadillo.move_table(  
  project,  
  folder,  
  name,  
  new_folder = folder,  
  new_name = name  
)
```

## Arguments

|            |                                                     |
|------------|-----------------------------------------------------|
| project    | a study or collection of variables                  |
| folder     | the folder containing the table to move             |
| name       | a table to move                                     |
| new_folder | the folder to move the table to, defaults to folder |
| new_name   | use to rename the file, defaults to name            |

## Value

NULL, invisibly

## Examples

```
## Not run:  
armadillo.move_table(  
  project = "gecko",  
  folder = "core_all",  
  name = "table1",  
  new_folder = "core_all_v2",  
)  
  
## End(Not run)
```

---

|                  |                                                            |
|------------------|------------------------------------------------------------|
| armadillo.subset | <i>Describes data available to subset and makes subset</i> |
|------------------|------------------------------------------------------------|

---

## Description

This automates the process of:

1. Checking what data is available to create subsets
2. Make the subset

## Usage

```
armadillo.subset(
  input_source = NULL,
  subset_def = NULL,
  source_project = NULL,
  source_folder = NULL,
  source_table = NULL,
  target_project = NULL,
  target_folder = NULL,
  target_table = NULL,
  target_vars = NULL,
  new_project = NULL,
  dry_run = NULL,
  strict = FALSE
)
```

## Arguments

|                |                                                                                                                                                                                        |
|----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| input_source   | Character specifying how information about the target view is provided: choose 'subset_def' if providing a subset definition object, or 'arguments' if providing information directly. |
| subset_def     | R object containing subset definition created by <code>armadillo.subset_definition()</code> . Compulsory if <code>input_source = 'subset_def'</code>                                   |
| source_project | project from which to subset data                                                                                                                                                      |
| source_folder  | folder from which to subset data. Compulsory if <code>input_source = 'arguments'</code> .                                                                                              |
| source_table   | table from which to subset data. Compulsory if <code>input_source = 'arguments'</code> .                                                                                               |
| target_project | project to upload subset to. Will be created if it doesn't exist.                                                                                                                      |
| target_folder  | folder to upload subset to. Will be created if it doesn't exist. Compulsory if <code>input_source = 'arguments'</code> .                                                               |
| target_table   | table to upload subset to. Compulsory if <code>input_source = 'arguments'</code> .                                                                                                     |
| target_vars    | variables from 'source_table' to include in the view. Compulsory if <code>input_source = 'arguments'</code> .                                                                          |
| new_project    | Deprecated: use <code>target_project</code> instead                                                                                                                                    |

|                      |                                                                                                                                                                                                          |
|----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>dry_run</code> | Defunct: previously enabled dry-run to check which variables are missing                                                                                                                                 |
| <code>strict</code>  | Boolean specifying whether to create subset if one or more target variables do not exist in the target data. Option FALSE will throw an error, option TRUE (default) creates subset and return a warning |

**Value**

missing variables provided in the subset definition

**Examples**

```
## Not run:
armadillo.subset(
  source_project = "gecko",
  target_project = "study1",
  subset_def = local_subset
)

## End(Not run)
```

---

`armadillo.subset_definition`

*Builds an R object containing info required to make subsets*

---

**Description**

Builds an R object containing info required to make subsets

**Usage**

```
armadillo.subset_definition(reference_csv = NULL, vars = NULL)
```

**Arguments**

|                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>reference_csv</code> | .csv file containing details of the variable to subset. Must contain 5 columns: 'source_folder' specifying the folder from which to subset, 'source_table' specifying the table from which to subset, 'target_folder' specifying the folder in which to create the subset, 'target_table' specifying the name of the subset and 'variable' specifying the variable(s) to include in the subset. Note that 'source_project' and 'target_project' are specified as arguments to 'armadillo.subset'. |
| <code>vars</code>          | Deprecated: use <code>reference_csv</code> instead                                                                                                                                                                                                                                                                                                                                                                                                                                                |

**Value**

A dataframe containing variables that is used for input in the `armadillo.subset()` method

**Examples**

```
## Not run:
armadillo.subset_definition(
  reference_csv = "C:/tmp/vars.csv"
)

## End(Not run)
```

---

armadillo.upload\_resource

*Uploads a resource to a folder in a project*

---

**Description**

Uploads a resource to a folder in a project

**Usage**

```
armadillo.upload_resource(project, folder, resource, name = NULL)
```

**Arguments**

|          |                                 |
|----------|---------------------------------|
| project  | the project to upload to        |
| folder   | the folder to upload to         |
| resource | the resource to upload          |
| name     | name of the resource (optional) |

**Examples**

```
## Not run:
armadillo.upload_table(
  project = "gecko",
  folder = "core_all",
  table1
)

## End(Not run)
```

---

`armadillo.upload_table`*Uploads a table to a folder in a project*

---

**Description**

Uploads a table to a folder in a project

**Usage**

```
armadillo.upload_table(project, folder, table, name = NULL)
```

**Arguments**

|                      |                              |
|----------------------|------------------------------|
| <code>project</code> | the project to upload to     |
| <code>folder</code>  | the folder to upload to      |
| <code>table</code>   | the table to upload          |
| <code>name</code>    | name of the table (optional) |

**Examples**

```
## Not run:  
armadillo.upload_table(  
  project = "gecko",  
  folder = "core_all",  
  table1  
)  
  
## End(Not run)
```

# Index

.add\_slash\_if\_missing, [2](#)  
.compress\_resource, [3](#)  
.compress\_table, [3](#)  
.format\_api\_posts, [4](#)  
.get\_linkfile\_content, [4](#)  
.load\_linked\_table, [5](#)  
.load\_resource, [5](#)  
.load\_table, [6](#)  
  
armadillo.copy\_resource, [6](#)  
armadillo.copy\_table, [7](#)  
armadillo.create\_project, [8](#)  
armadillo.delete\_project, [9](#)  
armadillo.delete\_project\_folder, [9](#)  
armadillo.delete\_resource, [10](#)  
armadillo.delete\_table, [10](#)  
armadillo.get\_project\_users, [11](#)  
armadillo.get\_projects\_info, [11](#)  
armadillo.install\_packages, [12](#)  
armadillo.list\_projects, [12](#)  
armadillo.list\_resources, [13](#)  
armadillo.list\_tables, [14](#)  
armadillo.load\_resource, [14](#)  
armadillo.load\_table, [15](#)  
armadillo.login, [16](#)  
armadillo.login\_basic, [16](#)  
armadillo.move\_resource, [17](#)  
armadillo.move\_table, [18](#)  
armadillo.subset, [19](#)  
armadillo.subset\_definition, [20](#)  
armadillo.upload\_resource, [21](#)  
armadillo.upload\_table, [22](#)