README for XFree86 4.2.1 on OpenBSD

Matthieu Herrb

Last modified on: 16 January 2002

1. What and Where is XFree86?

XFree86 is the Open Source port of X.Org's X11R6.6 release that supports several UNIX(R) and UNIX-like (such as Linux, the BSDs and Solaris x86) operating systems on Intel and other platforms.

See the Copyright Notice.

The sources for XFree86 4.2.1 are available by anonymous ftp from:

ftp://ftp.XFree86.org/pub/XFree86/4.2.1

Binaries for OpenBSD/i386 3.0 and later are available from:

ftp://ftp.XFree86.org/pub/XFree86/4.2.1/binaries/OpenBSD

A list of mirror sites is provided by http://www.xfree86.org/MIRRORS.shtml

XFree86 also builds on other OpenBSD architectures. See section *Building on other architectures* (section 8.2, page 5) for details.

2. Bug Reports for This Document

Send email to <herrb@xfree86.org> (Matthieu Herrb) or <XFree86@XFree86.org> if you have comments or suggestions about this file and we'll revise it.

3. New OS dependent features

See the Release Notes for non-OS dependent new features in XFree86 4.2.1.

3.1 New OS dependent features in 4.2

- Support for OpenBSD/macppc on the ATI Rage128 based Power Macintosh.
- Support for building clients on OpenBSD/sparc64.

3.2 New OS dependent features in 4.0.3

- Support for the wscons console driver in post 2.8 OpenBSD.
- A fix for multi-threaded libraries support.

3.3 New OS dependent features in 4.0.2

- Support for the OpenBSD ports tree,
- Preliminary support for the macppc architecture (clients build and work, the server doesn't work yet),
- xdm now writes an utmp entry,
- startx now creates an Xauthority magic cookie for the display.

3.4 New OS dependent features in 4.0.1

- Several features from the OpenBSD X11 tree were merged into xdm:
  - support for Kerberos IV authentication
  - use the arc4random(4) random number generator
  - add a new resource "allowRootLogin", which can be used to disable root logins through xdm
  - log failed logins to syslogd
  - verify that the shell is valid using /etc/shell
  - verify that the account hasn't expired
- The Xsun server can be built again on OpenBSD/sparc.

3.5 New OS dependent features in 4.0

- Multi-thread safe libraries are built by default on OpenBSD 2.6 and later,
- Preliminary APM support.

3.6 New OS dependent features in 3.9.18

- Support for USB mices has been added on OpenBSD.
- Soft-booting secondary cards through the int10 BIOS interface is now possible using the x86emu real mode emulator.

3.7 New OS dependent features in 3.9.17

- *Silken mouse* is supported for serial mices, and, under post 2.6 OpenBSD-current for PS/2 mices.
- MTRR Write Combining is enabled under post 2.6 OpenBSD-current.

4. Installing the Binaries

Refer to the Installation Document for detailed installation instructions.

5. Configuring X for Your Hardware

The `/etc/X11/XF86Config` file tells the X server what kind of monitor, video card and mouse you have. You *must* create it to tell the server what specific hardware you have.

You'll need info on your hardware:

- Your mouse type, baud rate and its /dev entry.
- The video card's chipset (e.g. ET4000, S3, etc).
- Your monitor's sync frequencies.

The recommended way to generate an `XF86Config` file is to use the `xf86cfg` utility. The

xf86config text utility is still there for the (few) cases where xf86cfg can't be used. Also, there is a sample file installed as `/usr/X11R6/lib/X11/XF86Config.eg`, which can be used as a starting point.

For details about the `XF86Config` file format, refer to the *XF86Config(5)* manual page.

Once you've set up a XF86Config file, you can fine tune the video modes with the `xvidtune` utility.

5.1 About mouse configuration

XFree86 4.2.1 has support for the mouse driver included in the new **wscons** console driver introduced by OpenBSD-2.9. Specify "`wsmouse`" as the protocol and "`/dev/wsmouse0`" as the device in `/etc/X11/XF86Config` if you're using OpenBSD-2.9 or later with a PS/2 or USB mouse.

See README.mouse for general instruction on mouse configuration in XFree86.

6. Running X

6.1 Starting xdm, the display manager

To start the display manager, log in as root on the console and type: "`xdm -nodaemon`".

You can start xdm automatically on bootup by changing the line

```
xdm_flags=NO            # for normal use: xdm_flags=""
```

to:

```
xdm_flags=""            # for normal use: xdm_flags=""
```

in `/etc/rc.conf`.

Note that the binary distributions of XFree86 for OpenBSD on ftp.xfree86.org and its mirrors don't include support for the XDM-AUTHORIZATION-1 protocol, because of the US export rules.

6.2 Running X without the display manager

The easiest way for new users to start X windows is to type: "`startx >& startx.log`". Error messages are lost unless you redirect them because the server takes over the screen.

To get out of X windows, type: "`exit`" in the console xterm. You can customize your X by creating `.xinitrc`, `.xserverrc`, and `.twmrc` files in your home directory as described in the xinit and startx man pages.

7. Kernel Support for X

To make sure X support is enabled under OpenBSD, the following line must be in your config file in `/sys/arch/i386/conf`:

```
option XSERVER
option APERTURE
```

7.1 Console drivers

The server supports the standard OpenBSD/i386 console drivers: pcvt and wscons. They are detected at runtime and no configuration of the server itself is required.

The pcvt console driver is the default in OpenBSD up to OpenBSD 2.8. It offers several virtual

consoles and international keyboard support.

OpenBSD 2.9 and later has switched to the wscons console driver. This console driver has a pcvt compatibility mode for X support.

7.2 Aperture Driver

By default OpenBSD includes the BSD 4.4 kernel security feature that disables access to the `/dev/mem` device when in multi-user mode. But the XFree86 server requires linear access to the display memory in most cases.

OpenBSD now requires the aperture driver to be enabled for all X servers, because the aperture driver also controls access to the I/O ports of the video boards.

To enable the aperture driver, once included in the kernel, set

```
machdep.allowaperture=2
```

in `/etc/sysctl.conf`. See the xf86(4) manual page for details.

Another (less recommended) way to enable linear memory and I/O ports access is to disable the kernel security feature by initializing `securelevel` to -1 in `/etc/rc.securelevel`.

> **Caveat:** the aperture driver only allows one access at a time (so that the system is in the same security state once X is launched). This means that if you run multiple servers on multiple virtual terminals, only the first one will have linear memory access. Set securelevel to −1 if you need more that one X server at a time.

7.3 MIT-SHM

OpenBSD supports System V shared memory. If XFree86 detects this support in your kernel, it will support the MIT-SHM extension.

To add support for system V shared memory to your kernel add the lines:

```
# System V-like IPC
options         SYSVMSG
options         SYSVSEM
options         SYSVSHM
```

to your kernel config file.

8. Rebuilding the XFree86 Distribution

You should configure the distribution by editing xc/config/cf/host.def before compiling. To compile the sources, invoke ‘‘make World’’ in the xc directory."

8.1 Console drivers

XFree86 has a configuration option to select the console drivers to use in `host.def`:

- if you’re using pccons only put:

  ```
  #define XFree86ConsoleDefines -DPCCONS_SUPPORT
  ```

- if you’re using pcvt only put:

  ```
  #define XFree86ConsoleDefines -DPCVT_SUPPORT
  ```

If you don’t define **XFree86ConsoleDefines** in `host.def` the pccons and pcvt drivers will be supported by default.

Native support for the wscons console driver found on OpenBSD/macppc and on OpenBSD/i386 2.9 and later is built by adding:

```
#define XFree86ConsoleDefines -DWSCONS_SUPPORT
```

to `xc/config/host.def` before rebuilding the server.

For the i386, you should include both pcvt and wscons support in order to use the pcvt compatibility mode of wscons:

```
#define XFree86ConsoleDefines -DPCVT_SUPPORT -DWSCONS_SUPPORT
```

8.2 Building on other architectures

XFree86 also compiles on other OpenBSD architectures.

Note that OpenBSD project now has its own source tree, based on the XFree86 source tree, with some local modifications. You may want to start with this tree to rebuild from sources. The OpenBSD XF4 source tree is available by anoncvs from all OpenBSD anoncvs servers. See http://www.openbsd.org/anoncvs.html for details on anoncvs.

8.2.1 XFree86 on OpenBSD/macppc

The XFree86 server is currently known to work on the G4 Macs and new iBooks with ATI Rage 128 cards running OpenBSD 3.0 or later. Other machines are more or less untested. Earlier OpenBSD versions lack some kernel support for it.

Use xf86config to build a /etc/X11/XF86Config file before starting the server for the first time.

Tou configure the keyboard, the protocol should be specified as **wskbd** and the device as `/dev/wskbd0`. Using a wsmux device as the keyboard device doesn't work (yet). Use **macintosh** as XkbModel.

For the Titanium Powerbook G4, you can try the following mode line in `/etc/X11/XF86Config` to match the flat panel resolution:

```
Modeline "1152x768" 78.741 1152 1173 1269 1440  768 769 772 800 +HSync +VSync
```

You need to set `securelevel` to -1 in the `/etc/rc.securelevel` configuration file to run XFree86 on OpenBSD/macppc.

9. Building New X Clients

The easiest way to build a new client (X application) is to use `xmkmf` if an `Imakefile` is included in the sources. Type "`xmkmf -a`" to create the Makefiles, check the configuration if necessary and type "`make`". Whenever you install additional man pages you should update `whatis.db` by running "`makewhatis /usr/X11R6/man`".

10. Thanks

Many thanks to all people who contributed to make XFree86 work on *BSD, in particular, **David Dawes**, **Pace Willison**, **Amancio Hasty**, **Christoph Robitschko**, **Nate Williams**, **Rod Grimes**, **Jack Velte** and **Michael Smith**.

CONTENTS

1. What and Where is XFree86? 1

2. Bug Reports for This Document 1

3. New OS dependent features 1
   - 3.1 New OS dependent features in 4.2 1
   - 3.2 New OS dependent features in 4.0.3 1
   - 3.3 New OS dependent features in 4.0.2 1
   - 3.4 New OS dependent features in 4.0.1 2
   - 3.5 New OS dependent features in 4.0 2
   - 3.6 New OS dependent features in 3.9.18 2
   - 3.7 New OS dependent features in 3.9.17 2

4. Installing the Binaries 2

5. Configuring X for Your Hardware 2
   - 5.1 About mouse configuration 3

6. Running X 3
   - 6.1 Starting xdm, the display manager 3
   - 6.2 Running X without the display manager 3

7. Kernel Support for X 3
   - 7.1 Console drivers 3
   - 7.2 Aperture Driver 4
   - 7.3 MIT-SHM 4

8. Rebuilding the XFree86 Distribution 4
   - 8.1 Console drivers 4
   - 8.2 Building on other architectures 5

9. Building New X Clients 5

10. Thanks 5

$XFree86: xc/programs/Xserver/hw/xfree86/doc/sgml/OpenBSD.sgml,v 1.24 2002/01/16 22:35:17 herrb Exp $