Release Notes for XFree86™ 4.2.1

The XFree86 Project, Inc

3 September 2002

Abstract

This document contains some information about features present in XFree86 4.2.1 and their status.

1. Introduction to the 4.x Release Series

XFree86 4.0 was the first official release of the new XFree86 4 series. XFree86 4.2.1 is the first update to 4.2.0, which is the latest full release in that series. XFree86 4 represents a significant redesign of the XFree86 X server. Not all of the hardware drivers from 3.3.x have been ported to 4.x yet, but conversely, 4.x has some hardware support not present in 3.3.x. Our Driver Status document summarizes how the hardware driver support compares between 3.3.6 and 4.2.1. Please check there first before downloading 4.2.1.

The 4.0.1 release introduced a new graphical configuration tool, "`xf86cfg`", and a text mode interface was added to it for the 4.0.2 release. It is work in progress, but definitely worth trying out. The trusty old text-based tool "`xf86config`" can also be used for generating X server config files. In addition to these tools, we've been working on a configuration tool that is built-in to the X server. It is included in the release, and it works well for some hardware. To try it out, just run (as root) "`XFree86 -configure`". Each of these configuration options will give you a reasonable starting point for a suitable configuration file. We've put some effort into documenting the 4.2.1 config file format, and you can find that information in the XF86Config manual page. Check that, the driver manual pages and the related documentation for further information.

Before you go to download and install the binary distributions for this release, please have a quick read through the Installation Document. It may save you some time and help you figure out which of the binary releases you need.

The next sections describe what has changed in the update release(s) as well as what is new in the latest full release (4.2.0). The other sections below describe some of the new features and changes between 3.3.x and 4.0. There are lot's of new features, and we definitely don't have enough space to cover them all here.

2. Summary of updates in 4.2.1.

2.1 Security

- Fix a zlib bug that may have security implications on some platforms.

- MIT-SHM update to not access SHM segments that the client doesn't have sufficient privileges to access.
- Fix an Xlib problem that made it possible to load (and execute) arbitrary code in privileged clients.

2.2 Other

- Revert the ATI driver's composite sync default to a safer value.
- Fix Xlib's modular i18n support on Solaris.
- Fix an X server crash when printing some types of modes.
- Startx and xon script fixes.
- Fix a colormap bug with 24+8 overlay mode.
- Update XDarwin support for the Jaguar release.
- Xaw bug fix.
- Fix a vesa driver floating point exception.
- Fix Emulate3Buttons for wsmouse protocol on NetBSD and OpenBSD.

3. Summary of new features in 4.2.0.

3.1 Video Driver Enhancements

- An s3 driver is added, which provides support for many of the older non-ViRGE and non-Savage S3 chipsets.
- Some vmware driver problems are fixed, and the driver is updated to take advantage of VMWare Workstation 3.0 features. These include improved hardware cursor handling and support for 8 bit emulation.
- Support added for Trident *BladeXP chipsets (currently not-accelerated).
- Xv support added for Trident TGUI series chips (not 9440 though).
- Support added for the older Trident chipsets again for ISA/VLBus (not tested)
- Support added to the glint driver for 3DLabs Permedia4, GLINT R4 and Gamma 2 chipsets.
- Support added to the i810 driver for Intel i830 (tested on Linux only).
- Support added to the ATI radeon driver for Radeon 7500 (2D and 3D), Radeon 8500 (2D only), and Rage128ProII.
- Support added for the Matrox G550 support. This included dual-head support.
- Support added for NVIDIA nForce integrated graphics.
- The NVIDIA nv driver now has preliminary powerpc support for the NV11 and NV20.
- Support added to the NVIDIA nv driver for interlaced modes on hardware that supports this, and support for resolutions higher than 1600x1200.
- Fixes for the savage driver on 64-bit platforms, XVideo support for the SuperSavage, and other savage driver updates.
- The ATI r128 driver now uses the CCE DMA engine for 2D acceleration when direct rendering is enabled, which reduces context switching overhead and improves stability and performance for XVideo and some 2D operations.

- The fbdev driver now supports rotation.
- Various updates to the apm, ark, chips (C&T), cirrus, i128, neomagic, newport, s3virge, siliconmotion, sis, tdfx, tseng, vesa, and vga drivers.

3.2 Input Driver Enhancements

- The mouse driver now has support for mouse wheel emulation.
- The mouse driver can now handle replug events on Linux for PS/2 mice.
- The "Min/Max X/Y Position" options in the elographics and mutouch drivers are changed to "Min/Max X/Y" to be consistent with the other input drivers.
- Linux USB keyboard access is fixed when no PS/2 controller is present.
- Added calcomp input driver.
- Added DMC input driver.
- Added hyperpen input driver.

3.3 X Server and Extension Updates

- Resynced with X.Org's X11R6.6.
- Mesa updated to the post-3.4.2 3.4 branch version as of November 2001.
- DRI drivers resynced with the latest from the DRI project.
- Various updates to the Xft library.
- The DEC-XTRAP extension is now available.
- The PEX and XIE extensions are no longer built/distributed by default.
- A security problem related to glyph clipping for large origins is fixed.
- An i810 XvMC (motion compensation) driver is now available (Linux only).
- A fatal bug XVideo Xineramification bug is fixed.

3.4 Client and Library Updates

- FreeType2 updated to version 2.0.6.
- Added libGL man pages.
- Xload now has support for displaying the load of remote hosts.
- Xterm updated to patch level 165.
- SuperProbe is removed.
- Sample xtrap clients added.

3.5 I18N and Font Updates

- New Luxi scalable fonts (TrueType and Type 1) from Bigelow & Holmes. These fonts are original designs by Kris Holmes and Charles Bigelow. See *below* (section 5.22, page 17) for further information.
- More locale/international keyboards supported.
- Modularized I18N support in Xlib is included from X11R6.6.
- A problem that caused bdftopcf to sometimes write corrupted fonts is fixed.

- Some problem with Xlib's handling of CTEXT and multi-byte characters are fixed.
- The fontenc layer is updated, and the fontenc library is now installed and available for other applications.
- Improvements to the input method framework in Xlib for UTF-8 locales.
- A filter called ''luit'' is added, which provides locale and ISO 2022 support to any Unicode terminal, notably xterm. Use of luit is still experimental in this release.

3.6 OS Support Updates

- Build problems on both QNX4 and QNX6 are fixed.
- VT switching problems with the i810 driver on FreeBSD are worked around.
- Problems building modules with some enhanced versions of gcc are fixed.
- Lots of updates for Darwin/Mac OS X, including:
  - On Mac OS X, a new rootless mode is added to the XDarwin X server. This allows X clients to display windows on the Aqua desktop.
  - Xinerama support added to XDarwin
  - With XDarwin in full screen mode, the depth, size, and refresh rate can now be chosen to be different from the settings used by Aqua.
  - GLX support added for Darwin and Mac OS X with software rendering.
  - Keymap setup in XDarwin is improved, particularly for international keyboards.
  - In addition to English and Japanese, the XDarwin user interface is now localized in Dutch, French, German, Spanish, and Korean.
- Lots of Cygwin support updates.
- Support added for OpenBSD/powerpc.
- Build support added for Linux on IBM S/390.
- Removed stale support for Amoeba and Minix.
- Client-side support added for sparc64 on NetBSD and OpenBSD.
- Support added for building the X server on Linux/m68k.
- Support added for building on Linux/arm32.
- Updates to Linux/mips support.

A more complete list of changes can be found in the CHANGELOG that is part of the XFree86 source tree. It can also be viewed online at our CVSweb server `<URL:http://cvsweb.xfree86.org/cvsweb/xc/programs/Xserver/hw/xfree86/CHANGELOG?rev=HEAD>`.

4. Drivers

4.1 Video Drivers

XFree86 4.2.1 includes the following video drivers:

Drivers marked with (*) are present in a preliminary form in this release, but are not complete and/or stable yet.

Drivers marked with (+) are for Linux/Sparc only.

Driver Name	Description	Further Information
apm	Alliance Pro Motion	README.apm
ark	Ark Logic	
ati	ATI	README.ati, README.r128, r128(4)
chips	Chips & Technologies	README.chips, chips(4)
cirrus	Cirrus Logic	
cyrix (*)	Cyrix MediaGX	README.cyrix
fbdev	Linux framebuffer device	fbdev(4)
glide	Glide2x (3Dfx)	glide(4)
glint	3Dlabs, TI	glint(4)
i128	Number Nine	README.I128, i128(4)
i740	Intel i740	README.i740
i810	Intel i810	README.i810, i810(4)
imstt	Integrated Micro Solns	
mga	Matrox	mga(4)
neomagic	NeoMagic	neomagic(4)
newport (-)	SGI Newport	README.newport, newport(4)
nv	NVIDIA	nv(4)
rendition	Rendition	README.rendition, rendition(4)
s3	S3 (not ViRGE or Savage)	
s3virge	S3 ViRGE	README.s3virge, s3virge(4)
savage	S3 Savage	savage(4)
siliconmotion	Silicon Motion	siliconmotion(4)
sis	SiS	README.SiS
sunbw2 (+)	Sun bw2	
suncg14 (+)	Sun cg14	
suncg3 (+)	Sun cg3	
suncg6 (+)	Sun GX and Turbo GX	
sunffb (+)	Sun Creator/3D, Elite 3D	
sunleo (+)	Sun Leo (ZX)	
suntcx (+)	Sun TCX	
tdfx	3Dfx	
tga	DEC TGA	README.DECtga
trident	Trident	trident(4)
tseng	Tseng Labs	
vesa	VESA	vesa(4)
vga	Generic VGA	vga(4)
vmware	VMWare guest OS	vmware(4)

Drivers marked with (-) are for Linux/mips only.

Darwin/Mac OS X uses IOKit drivers and does not use the module loader drivers listed above. Further information can be found in README.Darwin.

XFree86 4.2.1 includes the following input drivers:

4.2 Input Drivers

5. Overview of XFree86 4.x.

Unlike XFree86 3.3.x where there are multiple X server binaries, each of which drive different hardware, XFree86 4.2.1 has a single X server binary called XFree86. This binary can either have one or more video drivers linked in statically, or, more usually, dynamically load the video drivers and other modules that are needed.

XFree86 4.2.1 has X server support for most UNIX(R) and UNIX-like operating systems on

Driver Name	Description	Further Information
calcomp	Calcomp	
citron	Citron	citron(4)
digitaledge	DigitalEdge	
dmc	DMC	dmc(4)
dynapro	Dynapro	
elographics	EloGraphics	
hyperpen	HyperPen	
keyboard	generic keyboards	keyboard(4)
microtouch	MicroTouch	
mouse	most mouse devices	mouse(4)
mutouch	MicroTouch	
penmount	PenMount	
spaceorb	SpaceOrb	
summa	SummaGraphics	
void	dummy device	void(4)
wacom	Wacom tablets	wacom(4)

Intel/x86 platforms, plus support for Linux on Alpha, PowerPC, IA-64, Sparc, and Mips platforms, and for Darwin on PowerPC. Work on support for additional architectures and operating systems is in progress, and is planned for future releases.

5.1 Loader and Modules

The XFree86 X server has a built-in run-time loader, donated by Metro Link <URL:http://www.metrolink.com>. This loader can load normal object files and libraries in most of the commonly used formats. Since the loader doesn't rely on an operating system's native dynamic loader support, it works on platforms that don't provide this feature, and makes it possible for the modules to be operating system independent (although not, of course, independent of CPU architecture). This means that a module compiled on Linux/x86 can be loaded by an X server running on Solaris/x86, or FreeBSD, or even OS/2.

One of the main benefits of this loader is that when modules are updated, they do not need to be recompiled for every different operating system. In the future we plan to take advantage of this to provide more frequent driver module updates in between major releases.

The loader in version 4.2.1 has support for Intel (x86), Alpha and PowerPC platforms. It also has preliminary support for Sparc platforms.

The X server makes use of modules for video drivers, X server extensions, font rasterisers, input device drivers, framebuffer layers (like mfb, cfb, etc), and internal components used by some drivers (like XAA),

The module interfaces (API and ABI) used in this release is still subject to change without notice. While we will attempt to provide backward compatibility for the module interfaces as of the 4.0 release (meaning that 4.0 modules will work with future core X server binaries), we cannot guarantee this.

Note about module security

> The XFree86 X server runs with root privileges, i.e. the X server loadable modules also run with these privileges. For this reason we recommend that all users be careful to only use loadable modules from reliable sources, otherwise the introduction of viruses and contaminated code can occur and wreak havoc on your system. We hope to have a mechanism for signing/verifying the modules that we provide available in a future release.

5.2 Configuration File

The X server configuration file format has been extended to handle some of the new functionality. The `xf86config` utility can be used to generate a basic config file, that may require some manual editing. The X server also has preliminary support for generating a basic config file. This is done by running (as root) "`XFree86 -configure`". Alternatively, the sample config file `XF86Config.eg` that is installed in `/usr/X11R6/lib/X11` may be used as a starting point. The `xf86cfg` utility can also be used to create a new configuration file or to edit an existing one. The `XF86Setup` utility is currently not usable, but work is continuing in this area.

The main changes are covered here, but please refer to the XF86Config(5) manual page for more comprehensive information:

- The Module section is used to load server extension modules and font modules, but not XInput drivers. The `.so` suffix should no longer be specified with module names. Options may be supplied for modules by loading the module via a SubSection instead of the usual Load keyword. The `bitmap` module is the only font module that is loaded by default. No server extensions are loaded by default, but some are built-in to the server. It is strongly recommended that the extension module containing a range of small miscellaneous extensions (`extmod`) be loaded because some commonly used things won't work correctly without it. The following example shows how to load all the server extensions plus the Type1 and TrueType fonts support, and a commented example that shows how to pass options to an extension (this one is for loading the misc extensions (`extmod`) with the XFree86-VidModeExtension disabled):

```
Section "Module"

    Load "dbe"
    Load "record"
    Load "glx"
    Load "extmod"

    Load "type1"
    Load "freetype"

  # SubSection "extmod"
  #     Option "Omit XFree86-VidModeExtension"
  # EndSubSection

EndSection
```

- Option flags have been extended and are now used more widely in the config file. Options flags come in two main types. The first type is exactly like the old form:

```
Option "name"
```

  where the option just has a name specified. The name is case insensitive, and white space and underscore characters are ignored. The second type consists of a name and a value:

```
Option "name" "value"
```

The value is passed transparently as a string to the code that uses the option. Common value formats are integer, boolean, real, string and frequency. The following boolean option values are recognised as meaning TRUE: `"true"`, `"yes"`, `"on"`, `"1"`, and no value. The values recognised as FALSE are `"false"`, `"no"`, `"off"`, `"0"`. In addition to this, `"no"` may be prepended to the *name* of a boolean option to indicate that it is false. Frequency options can have the strings `Hz`, `kHz`, or `MHz` appended to the numerical value specified.

Note: the value must always be enclosed in double quotes (`"`), even when it is numerical.

- The ServerFlags section now accepts its parameters as Options instead of as special keywords. The older keyword format is still recognised for compatibility purposes, but is deprecated and support for it will likely be dropped in a future release. The DPMS and screen save timeout values are now specified in the ServerFlags section rather than elsewhere (because they are global parameters, not screen-specific). This example shows the defaults for these:

```
    Option "blank time"    "10"
    Option "standby time"  "20"
    Option "suspend time"  "30"
    Option "off time"      "40"
```

The new option `AllowDeactivateGrabs` allows deactivating any active grab with the key sequence `Ctrl+Alt+Keypad-Divide` and the new option `AllowClosedownGrabs` allows closing the conection to the grabbing client with the key sequence `Ctrl+Alt+Keypad-Multiply`. Note that these options are off by default as they allow users to remove the grab used by screen saver/locker programs.

- The Keyboard, Pointer and XInput sections have been replaced by a more general InputDevice section. The old Keyboard and Pointer sections are still recognised for compatibility purposes, but they are discommended and support for them may be dropped in future releases. The old XInput sections are no longer recognised. The keywords from the old sections are expressed as Options in the InputDevice sections. The following example shows typical InputDevice sections for the core mouse and keyboard.

```
Section "InputDevice"
    Identifier  "Keyboard 1"
    Driver      "keyboard"
    Option      "AutoRepeat" "500 5"
    Option      "XkbModel"   "pc104"
    Option      "XkbLayout"  "us"
EndSection

Section "InputDevice"
    Identifier  "Mouse 1"
    Driver      "mouse"
    Option      "Protocol"   "PS/2"
    Option      "Device"     "/dev/mouse"
    Option     "SampleRate" "80"
EndSection
```

- The Monitor section is mostly unchanged. The main difference is that a set of VESA modes is defined internally in the server, and so for most monitors, it isn't necessary to specify any modes explicitly in the Monitor section. There is also a new Modes section that can be used

to define a set of modes separately from the Monitor section, and the Monitor section may "include" them with the "UseModes" keyword. The Monitor section may also include Options. Options that are monitor-specific, like the "DPMS" and "Sync on Green" options are best specified in the Monitor sections.

- The Device sections are mostly unchanged. The main difference is the new (and mandatory) Driver keyword that specifies which video driver should be loaded to drive the video card. Another difference is the BusID keyword that is used to specify which of possibly multiple video cards the Device section is for. The following is an example for a Matrox card:

```
Section "Device"
    Identifier "MGA 1"
    Driver     "mga"
    BusID      "PCI:1:0:0"
EndSection
```

- The Screen sections are mostly unchanged. The old Driver keyword is no longer used, and a mandatory Identifier keyword has been added. The DefaultColorDepth keyword has been renamed to DefaultDepth.
- A new section called ServerLayout has been added to allow the layout of the screens and the selection of input devices to be specified. The ServerLayout sections may also include options that are normally found in the ServerFlags section. Multiple ServerLayout sections may be present, and selected from the command line. The following example shows a ServerLayout section for a dual-headed configuration with two Matrox cards, and two mice:

```
Section "ServerLayout"
    Identifier  "Layout 1"
    Screen      "MGA 1"
    Screen      "MGA 2" RightOf "MGA 1"
    InputDevice "Keyboard 1" "CoreKeyboard"
    InputDevice "Mouse 1"    "CorePointer"
    InputDevice "Mouse 2"    "SendCoreEvents"
    Option      "BlankTime"  "5"
EndSection
```

See the XF86Config man page for a more detailed explanation of the format of the new ServerLayout section.

The config file search patch has been extended, with the directories /etc/X11 and /usr/X11R6/etc/X11 being added. The full search path details are documented in the XF86Config manual page.

5.3 Command Line Options

The following new X server command line options have been added:

-depth *n*

This specifies the colour depth that the server is running at. The default is 8 for most drivers. Most drivers support the values 8, 15, 16 and 24. Some drivers also support the values 1 and 4. Some drivers may also support other depths. Note that the depth is different from the ‘‘bpp’’ that was specified with previous versions. The depth is the number of bits in each pixel that are significant in determining the pixel’s value. The bpp is the total size occupied by each pixel, including bits that are not used. The old -bpp option is no longer recognised because it isn’t a good way of specifying the server behaviour.

-fbbpp *n*

This specifies the bpp format to use for the framebuffer. This may be used in 24-bit mode to force a framebuffer format that is different from what the driver chooses by default. In most cases there should be no need to use this option.

-pixmap24

This specifies that the client-side pixmap format should be the packed 24-bit format that was often used by the 3.3.x servers. The default is the more common 32-bit format. There should normally be no need to use this option.

-pixmap32

This specifies that the client-side pixmap format should be the sparse 32-bit format. This is the default, so there should normally be no need to use this option.

-layout *name*

This specifies which ServerLayout section in the config file to use. When this option is not specified, the first ServerLayout section is used. When there is no ServerLayout section, the first Screen section is used.

-screen *name*

This specifies which Screen section in the config file to use. When this option is not specified, the first ServerLayout section is used. When there is no ServerLayout section, the first Screen section is used.

-keyboard *name*

This specifies which InputDevice section in the config file to use for the core keyboard. This option may be used in conjunction with the -screen option.

`-pointer` *name*

This specifies which InputDevice section in the config file to use for the core pointer. This option may be used in conjunction with the -screen option.

`-modulepath` *path*

This specifies the module search path. The path should be a comma-separated list of absolute directory paths to search for server modules. When specified here, it overrides the value specified in the config file. This option is only available when the server is started by the root user.

`-logfile` *file*

This specifies the log file name. When specified here, it overrides the default value. This option is only available when the server is started by the root user.

`-scanpci`

This specifies that the scanpci module should be loaded and executed. This does a scan of the PCI bus.

`-logverbose` [*n*]

This options specifies the verbosity level to use for the log file. The default is 3.

The following X server command line options have been changed since 3.3.x:

`-verbose` [*n*]

This option specifies the verbosity level to use for the server messages that get written to stderr. It may be specified multiple times to increase the verbosity level (as with 3.3.x), or the verbosity level may be specified explicitly as a number. The default verbosity level is 0.

`-xf86config` *filename*

This option has been extended to allow non-root users to specify a relative config file name. The config file search path will be used to locate the file in this case. This makes it possible for users to choose from multiple config files that the the sysadmin has provided.

A more complete list of XFree86 X server command line options can be found in the XFree86(1) manual page.

5.4 XAA

The XFree86 Acceleration Architecture (XAA) has been completely rewritten from scratch for XFree86 4.x. Most drivers implement acceleration by making use of the XAA module.

5.5 Multi-head

Some multi-head configurations are supported in XFree86 4.x, primarily with multiple PCI/AGP cards. However, this is an area that is still being worked on, and we expect that the range of configurations for which it works well will increase in future releases. A configuration that is known to work well in most cases is multiple (supported) Matrox cards.

One of the main problems is with drivers not sufficiently initialising cards that were not initialised at boot time. This has been improved somewhat with the INT10 support that is used by most drivers (which allows secondary card to be "soft-booted", but in some cases there are other issues that still need to be resolved. Some combinations can be made to work better by changing which card is the primary card (either by using a different PCI slot, or by changing the system BIOS's preference for the primary card).

5.6 Xinerama

Xinerama is an X server extension that allows multiple physical screens to behave as a single screen. With traditional multi-head in X11, windows cannot span or cross physical screens. Xinerama removes this limitation. Xinerama does, however, require that the physical screens all have the same root depth, so it isn't possible, for example, to use an 8-bit screen together with a 16-bit screen in Xinerama mode.

Xinerama is not enabled by default, and can be enabled with the `+xinerama` command line option for the X server.

Xinerama was included with X11R6.4. The version included in XFree86 4.x was completely rewritten for improved performance and correctness.

Known problems:

- Most window managers are not Xinerama-aware, and so some operations like window placement and resizing might not behave in an ideal way. This is an issue that needs to be dealt with in the individual window managers, and isn't specifically an XFree86 problem.

5.7 DGA version 2

DGA 2.0 is included in 4.2.1, but is not implemented by all drivers. Preliminary documentation for the client libraries can be found in the `README.DGA` document. A good degree of backwards compatibility with version 1.0 is provided.

5.8 DDC

The VESA(R) Display Data Channel (DDC™) standard allows the monitor to tell the video card (or on some cases the computer directly) about itself; particularly the supported screen resolutions and refresh rates.

Partial or complete DDC support is available in most of the video drivers. DDC is enabled by default, but can be disabled with a "Device" section entry: `Option "NoDDC"`. We have support for DDC versions 1 and 2; these can be disabled independently with `Option "NoDDC1"` and `Option "NoDDC2"`.

At startup the server prints out DDC information from the display, and can use this information to set or warn about monitor sync limits (but not modelines yet). For some drivers, the X server's new `-configure` option uses the DDC information when generating the config file.

5.8.1 Changed behavior caused by DDC.

Several drivers uses DDC information to set the screen size and pitch. This can be overridden by explicitly resetting it to the and non-DDC default value 75 with the `-dpi 75` command line option for the X server, or by specifying appropriate screen dimensions with the "DisplaySize" keyword in the "Monitor" section of the config file.

5.9 GLX and the Direct Rendering Infrastructure (DRI)

Precision Insight <URL:http://www.precisioninsight.com> was provided with funding and support from Red Hat <URL:http://www.redhat.com>, SGI <URL:http://www.sgi.com>, 3Dfx <URL:http://www.3dfx.com>, Intel <URL:http://www.intel.com>, ATI <URL:http://www.ati.com>, and Matrox <URL:http://www.matrox.com> to integrate the GLX extension for 3D rendering in an X11 window. The 3D core rendering component is the Mesa <URL:http://www.mesa3d.org> library. SGI has released the sources to the GLX extension framework under an open license, which essentially provides the glue between the 3D library and this windowing system. Precision Insight has integrated these components into the XFree86 X Server and added a Direct Rendering Infrastructure (DRI). Direct Rendering provides a highly optimized path for sending 3D data directly to the graphics hardware. This release provides a complete implementation of direct rendering support for the 3Dfx Banshee, Voodoo3 and Voodoo5 graphics cards, as well as the Intel i810/i815 cards, ATI Rage 128, and Matrox G400. Updated information on DRI compatible drivers can be found at the DRI Project <URL:http://dri.sourceforge.net> on SourceForge <URL:http://www.sourceforge.net>.

5.10 XVideo Extension (Xv)

The XVideo extension is supported in XFree86 4.x. An XvQueryPortAttributes function has been added as well as support for XvImages. XvImages are XImages in alternate color spaces such as YUV and can be passed to the server through shared memory segments. This allows clients to display YUV data with high quality hardware scaling and filtering.

5.11 X Rendering Extension (Render)

The X Rendering extension provides a 2D rendering model that more closely matches application demands and hardware capabilities. It provides a rendering model derived from Plan 9 based on Porter/Duff image composition rather than binary raster operations.

Using simple compositing operators provided by most hardware, Render can draw anti-aliased text and geometric objects as well as perform translucent image overlays and other image operations not possible with the core X rendering system.

XFree86 4.2.1 provides a partial implementation of Render sufficient for drawing anti-aliased text and image composition. Still to be implemented are geometric primitives and affine transformation of images.

Unlike the core protocol, Render provides no font support for applications, rather it allows applications to upload glyphs for display on the screen. This allows the client greater control over text rendering and complete access to the available font information while still providing hardware acceleration. The Xft library provides font access for Render applications.

5.11.1 The Xft Library

On the client side, the Xft library provides access to fonts for applications using the FreeType library, version 2. FreeType currently supports Type1 and TrueType font files, a future release is expected to support BDF and PCF files as well, so Render applications will have access to the complete range of fonts available to core applications. One important thing to note is that Xft uses the vertical size of the monitor to compute accurate pixel sizes for provided point sizes; if your monitor doesn't provide accurate information via DDC, you may want to add that

information to `XF86Config`.

To allow a graceful transition for applications moving from core text rendering to the Render extension, Xft can use either core fonts or FreeType and the Render extension for text. By default, Xft is configured to support both core fonts and FreeType fonts using the supplied version of FreeType 2. See the section on FreeType support in Xft for instructions on configuring XFree86 to use an existing FreeType installation.

The Xft library uses a configuration file, `XftConfig`, which contains information about which directories contain font files and also provides a sophisticated font aliasing mechanism. Documentation for that file is included in the Xft man page.

5.11.2 FreeType support in Xft

XFree86 4.2.1 includes sources for FreeType version 2.0.6, and, by default, they are built and installed automatically.

If you prefer, you can configure XFree86 4.2.1 to use an existing Freetype2 installation by telling XFree86 not to build the internal copy and indicating where that external version has been installed. Edit (or create) `config/cf/host.def` to include:

- `#define BuildFreetype2Library NO`
- `#define Freetype2Dir /usr/local`

Note that XFree86 assumes you'll be using a release FreeType no older than version 2.0.1. Early FreeType version 2 releases used a different header file installation and aren't compatible with XFree86. Instructions for building and installing FreeType can be found in the `INSTALL` file included with the FreeType release.

5.11.3 Application Support For Anti-Aliased Text

Only three applications have been modified in XFree86 4.2.1 to work with the Render extension and the Xft and FreeType libraries to provide anti-aliased text. Xterm, xditview and x11perf. Migration of other applications may occur in future releases.

By default, xterm uses core fonts through the standard core API. It has a command line option and associated resource to direct it to use Xft instead:

- `-fa` family / `.VT100.faceName:` family. Selects the font family to use.

Xditview will use Xft instead of the core API by default. X11perf includes tests to measure the performance of text rendered in three ways, anti-aliased, anti-aliased with sub-pixel sampling and regular chunky text, but through the Render extension, a path which is currently somewhat slower than core text.

5.12 Other extensions

The XFree86-Misc extension has not been fully ported to the new server architecture yet. This should be completed in a future release.

The XFree86-VidModeExtension extension has been updated, and mostly ported to the new server architecture. The area of mode validation needs further work, and the extension should be used with care. This extension has support for changing the gamma setting at run-time, for modes where this is possible. The `xgamma` utility makes use of this feature. Compatibility with the 3.3.x version of the extension is provided. The missing parts of this extension and some new features should be completed in a future release.

5.13 Xaw

Two versions of the Xaw library are provided with XFree86 4.x. A version with bug fixes and a few binary compatible improvements and a new version with several new features.

New features:

- A `displayList` resource is available to all Xaw widgets. It basically consists of a list of drawing commands, fully described in the `Xaw(3)` manual page, that enables a integration of Xaw programs with the new window/desktop managers that allows for configurable themes.
- Some new actions were added to all Xaw widgets, to allow more configurable control of the widgets, and to allow setting resources at run time.
- Since Xpm was integrated into XFree86, programs linked with the new Xaw library will also link with Xpm. This allows for color background pixmaps, and also for shaped widgets.
- The text widget is the widget that will present more changes. These include:
  - Block cursor.
  - Compile time limit of 16384 undo/redo levels (that will automatically grow if the text is not saved when this mark is reached).
  - Overwrite mode.
  - Text killed is inserted in a kill ring list, this text is not forgotten, pressing `M-y` allows traversing the kill ring list.
  - International support for latin languages is available even if the `international` resource is not set. Users will need to properly set the *locale* environment to make complete use of this feature.
  - A better `multiply` interface is provided. Pressing `C-u,<number>` (where number can be negative) allows passing parameters for text actions.
  - Text can be formatted to have left, right, center or full justification.
  - Text indentation support is also available.

Bug fixes:

- The simple menu widget geometry management code was improved to solve problems with menu entries not visible in the screen.
- The form widget geometry code was changed to solve problems with integer round problems in the child widgets geometry when resizing the parent form widget.
- Several bugs were fixed in the text code, while some code was rewritten from scratch.

5.14 Xpm

Version 3.4k of the Xpm (X pixmap) library is now integrated into XFree86.

5.15 xedit

Xedit have been changed to use most of the new features added to the new version of the Xaw library, and some xedit only features were added. Emacs users will find that several of the emacs key bindings work with the new version of xedit. These include:

- File name tab completion. Including a *Emacs dired* like window, that will be shown when there are more than one match, when `C-x,d` is pressed, or when a directory name is specified.

- An unlimited number of files can be edited at the same time. Including multiple views of the same or different files.
- The line number of the cursor position is always visible. It can also be customized to show the column number, the position offset and the current size of the file.
- There is an `autoReplace` resource, that enables automatic text replacement at the time text is typed. This feature is useful to create simple macros, or to correct common spelling errors.
- A fully featured ispell interface is also available. This interface is expected to provide most of the features of the terminal interface of the ispell program, with some extra features that include:
    - A compile time limit of 16 undo levels.
    - Terse mode switch.
    - Dictionary change.
    - The interface also checks for repeated words.
- A first tentative to add programming modes was done. Currently, there is one mode:
    - **C-mode:** this mode is expected to be stable, and fully usable.

5.16 Font support

Details about the font support in XFree86 4.x can be found in the README.fonts document.

5.17 TrueType support

XFree86 4.x comes with two TrueType backends, known as 'xfsft' (the `"freetype"` module) and 'X-TrueType' (the `"xtt"` module). Both of these backends are based on the FreeType library.

5.18 CID font support

Support for CID-keyed fonts is included in XFree86 4.x. The CID-keyed font format was designed by Adobe Systems `<URL:http://www.adobe.com>` for fonts with large character sets. The CID-keyed font support in XFree86 was donated by SGI `<URL:http://www.sgi.com>`. See the LICENSE document for a copy of the CID Font Code Public License.

5.19 Internationalisation of the scalable font backends

XFree86 4.x has a ''fontenc'' layer to allow the scalable font backends to use a common method of font re-encoding. This re-encoding makes it possible to uses fonts in encodings other than their their native encoding. This layer is used by the Type1 and Speedo backends and the 'xfsft' version of the TrueType backend. The 'X-TrueType' version of the TrueType backend uses a different re-encoding method based on loadable encoding modules.

5.20 Large font optimisation

The glyph metrics array, which all the X clients using a particular font have access to, is placed in shared memory, so as to reduce redundant memory consumption. For non-local clients, the glyph metrics array is transmitted in a compressed format.

5.21 Unicode/ISO 10646 support

What is included in 4.x:

- All ''-misc-fixed-*'' BDF fonts are now available in the ISO10646-1 encoding and cover at least the 614 characters found in ISO 8859-{1-5,7-10,14,15}, CP1252, and MES-1. The non-bold fonts also cover all Windows Glyph List 4 (WGL4) characters, including those found in all 8-bit MS-DOS/Windows code pages. The 8-bit variants of the ''-misc-fixed-*'' BDF fonts (ISO8859-1, ISO8859-2, KOI8-R, etc.) have all been automatically generated from the new ISO10646-1 master fonts.
- Some ''-misc-fixed-*'' BDF ISO10646-1 fonts now cover a comprehensive Unicode repertoire of over 3000 characters including all Latin, Greek, Cyrillic, Armenian, Gregorian, Hebrew, IPA, and APL characters, plus numerous scientific, typographic, technical, and backwards-compatibility symbols. Some of these fonts also cover Arabic, Ethiopian, Thai, Han/Kanji, Hangul, full ISO 8859, and more. For the 6x13 font there is now a 12x13ja Kanji extension and for the 9x18 font there is a 18x18ja Kanji/Han/Hangul extension, which covers all ISO-2022-JP-2 (RFC 1554) characters. The 9x18 font can also be used to implement simple combining characters by accent overstriking. For more information, read Markus Kuhn's UTF-8 and Unicode FAQ `<URL:http://www.cl.cam.ac.uk/~mgk25/unicode.html>`.
- Mark Leisher's ClearlyU proportional font (similar to Computer Modern).
- ISO 10646/Unicode UTF-8 Level 1 support added to xterm (enabled with the `-u8` option).
- Both the xfsft (the `"freetype"` module) and the X-TrueType (the `"xtt"` module) TrueType font backends support Unicode-encoded fonts.

5.22 Luxi fonts from Bigelow and Holmes

XFree86 now includes the ''Luxi'' family of Type 1 fonts and TrueType fonts. This family consists of the fonts ''Luxi Serif'', ''Luxi Sans'' and ''Luxi Mono'' in Roman, oblique, bold and bold oblique variants. The TrueType version have glyphs covering the basic ASCII Unicode range, the Latin 1 range, as well as the *Extended Latin* range and some additional punctuation characters. In particular, these fonts include all the glyphs needed for ISO 8859 parts 1, 2, 3, 4, 9, 13 and 15, as well as all the glyphs in the Adobe Standard encoding and the Windows 3.1 character set.

The glyph coverage of the Type 1 versions is somewhat reduced, and only covers ISO 8859 parts 1, 2 and 15 as well as the Adobe Standard encoding.

The Luxi fonts are original designs by Kris Holmes and Charles Bigelow from Bigelow and Holmes Inc., who developed the Luxi typeface designs in Ikarus digital format. URW++ Design and Development GmbH converted the Ikarus format fonts to TrueType and Type 1 font programs and implemented the grid-fitting "hints" and kerning tables in the Luxi fonts.

The license terms for the Luxi fonts are included in the file '`COPYRIGHT.BH`', as well as in the License document. For further information, please contact <design@bigelowandholmes.com> or <info@urwpp.de>, or consult the URW++ web site `<URL:http://www.urwpp.de>`.

5.23 Directory rearrangements

Some changes to the installed XFree86 directory structure have been implemented for 4.x. One important change is a modified search path for the X server's `XF86Config` file. The details of this can be found in the XF86Config manual page. The other main change is moving most of the run-time configuration files to `/etc/X11`, with symbolic links in the old `/usr/X11R6/lib/X11` location pointing to the new location. Some run-time generated files are now located under the appropriate subdirectories of `/var`, again with the relevant symbolic links in the old location.

CONTENTS

1. Introduction to the 4.x Release Series 1

2. Summary of updates in 4.2.1. 1
   2.1 Security 1
   2.2 Other 2

3. Summary of new features in 4.2.0. 2
   3.1 Video Driver Enhancements 2
   3.2 Input Driver Enhancements 3
   3.3 X Server and Extension Updates 3
   3.4 Client and Library Updates 3
   3.5 I18N and Font Updates 3
   3.6 OS Support Updates 4

4. Drivers 4
   4.1 Video Drivers 4
   4.2 Input Drivers 5

5. Overview of XFree86 4.x. 5
   5.1 Loader and Modules 6
   5.2 Configuration File 7
   5.3 Command Line Options 9
   5.4 XAA 12
   5.5 Multi-head 12
   5.6 Xinerama 12
   5.7 DGA version 2 12
   5.8 DDC 12
   5.9 GLX and the Direct Rendering Infrastructure (DRI) 13
   5.10 XVideo Extension (Xv) 13
   5.11 X Rendering Extension (Render) 13
   5.12 Other extensions 14
   5.13 Xaw 14
   5.14 Xpm 15
   5.15 xedit 15
   5.16 Font support 16
   5.17 TrueType support 16
   5.18 CID font support 16
   5.19 Internationalisation of the scalable font backends 16
   5.20 Large font optimisation 16
   5.21 Unicode/ISO 10646 support 17
   5.22 Luxi fonts from Bigelow and Holmes 17
   5.23 Directory rearrangements 17

$XFree86: xc/programs/Xserver/hw/xfree86/doc/sgml/RELNOTES.sgml,v 1.70.2.2 2002/09/04 03:01:48 da